

Constant current power supply unit not dimm. IP68 24W with 2 outgoing cables L = 400 - I out = 500 mA - Dimensions = 122x54x26 mm

Last information update: November 2024

Accessory code

X645: Constant current power supply unit not dimm. IP68 24W with 2 outgoing cables L = 400 - I out = 500 mA - Dimensions = 122x54x26 mm



Technical description

Constant current non-dimmable electronic ballast I=500 mA 24 W. Input Vin=220÷240 Vac 50÷60 Hz. SELV output. The product features include a high level of mains spike protection, 4 kV differential mode, 4 kV common mode, short circuit protection, overcurrent and overtemperature protection. Usage temperature: -40°C / +60°C.

Installation

Positioned on top of or inside boxes with suitable drainage. Fitted with slots for fastening with screws, if required.

Colour	Weight (Kg)	Dimension (mm) (*)
Indeterminate (00)	0.3	122x54x26
* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.		

Wiring

Fitted with 2 x 400 mm long primary and secondary outlet cables.

Notes

SELV, EL

Complies with EN60598-1 and pertinent regulations



Technical data

Frequency [Hz]:	50/60	Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 31 power supply units B16A: 50 power supply units C10A: 52 power supply units C16A: 85 power supply units
Current out [mA]:	500		
Inrush current:	5 A / 50 µs		
Overvoltage protection:		4kV Common mode & 4kV Differential mode	