


Wooden pole

Last information update: April 2025



Accessory code

X922: Conical pole with square base and cylindrical end made of wood with plate - Total H 6000mm - base dimension 160x160mm - final diameter Ø100mm - spigot diameter Ø76mm

Technical description

Conical wooden pole with a 160x160mm square base and a cylindrical end section with a Ø100mm final diameter with a steel base and end section. The steel part (H=1400mm) is hot-galvanised and powder painted to guarantee durability in compliance with the EN ISO 1461 standard. It is fitted with a flush access cover measuring 400x85mm and located 500mm above the ground. The central part of the pole is made of stacked pinewood sheets that are compressed, high-resistance glued and refined with specific treatments for adapting to and resisting UV rays, damp and changes in weather conditions. The first treatment protects the wood from mould and the second gives it a gloss finish. The lamellar structure minimizes the contractions/expansions caused by moisture changes. All the wood used is PEFC (Program for the Endorsement of Forest Certification) certified. The pole allows products to be pole-top, single side or double side-mounted according to the choice of slot detail in the catalogue.

Installation

The diameter of the pole-top, single side and double side attachment is Ø76mm.

Colour

Cinnamon / Silver Grey (M8) | Cinnamon / Grey Sand (M9) | Cinnamon / Graphite Grey (N1) | Saffron / Silver Grey (N2) | Saffron / Grey Sand (N3) | Saffron / Graphite Grey (N4) | Onyx / Silver Grey (N5) | Onyx / Grey Sand (N6) | Onyx / Graphite Grey (N7)

Flange Drilling

Pole - Top (FL) | Single Lateral (FM) | Double Lateral (FN)

Complies with EN60598-1 and pertinent regulations

