

## iN60 Evo Stand-alone

Design iGuzzini

iGuzzini

Last information update: February 2025

### Product configuration: RY92.L2

RY92.L2: Pendant-mounted Stand Alone - Neutral White LED - Up/Down - DALI - GL - HO - Opal - L=1200 - 40W 4972.5lm - 4000K - CRI 90 - White / Opal White

### Product code

RY92.L2: Pendant-mounted Stand Alone - Neutral White LED - Up/Down - DALI - GL - HO - Opal - L=1200 - 40W 4972.5lm - 4000K - CRI 90 - White / Opal White

### Technical description

Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. Neutral White LED plate with direct (Down) and indirect (Up) light emission. High Output (HO) version for General Light profiles. The module optic and structural fittings combined with the use of a "Furukawa" flow recovery unit allow high system efficiency values to be achieved. DALI dimmable power supply integrated in the luminaire. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Opal PMMA diffuser screen. Pendant and power supply cables L=1500

### Installation

Pendant-mounted

### Colour

White / Opal White (L2)

Complies with EN60598-1 and pertinent regulations



### Technical data

lm system:	4973	Colour temperature [K]:	4000
W system:	40	MacAdam Step:	3
lm source:	6630	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	36	Lamp code:	LED
Luminous efficiency (lm/W, real value):	124.3	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	2010	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	75	Control:	DALI-2
CRI (minimum):	90		

### Polar

