


Last information update: October 2024



**Product code**

2169: 5 - cell Recessed luminaire - LED - Warm white - Incorporated DALI dimmable power supply - Flood optic

**Technical description**

rectangular miniaturised recessed luminaire with 5 optical elements with LED lamps - fixed optics - flood beam angle. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare . Supplied with DALI dimmable electronic control gear connected to the luminaire. Warm white high colour rendering LED.

**Installation**

recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 141

**Colour**

White (01) | Black / Black (43) | Black / White (47)

**Weight (Kg)**

0.3


**Mounting**

wall recessed|ceiling recessed

**Wiring**

on control gear box; screw connections with terminal block included

Complies with EN60598-1 and pertinent regulations



**Technical data**

lm system:	-	CRI:	90
W system:	10 (*)	Colour temperature [K]:	2700
lm source:	-	Number of lamps for optical assembly:	1
W source:	10 (*)	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1
Beam angle [°]:	32° (*)	Control:	DALI-2