

View Opti Beam Lens round


Design iGuzzini /
Arup

iGuzzini

Last information update: March 2025

Product configuration: 414B

414B: round small body spotlight - medium



Product code

414B: round small body spotlight - medium

Technical description

Indoor adjustable spotlight with adapter for installation on a three-phase/DALI track. Device made of die-cast aluminium and a front part made of a thermoplastic material. Spotlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Optical assembly consisting of Warm White tone 3000K CRI90 LEDs with OPTIBEAM LENS technology and a well-defined medium light beam. Dimmable DALI driver built-in to box with a semi-hidden system on track. Option of installing a range of flat accessories including an OPTIBEAM REFRACTOR for varying light distribution, an elliptical distribution refractor, a louver, a soft lens and an outdoor accessory like an asymmetric visor for eliminating stray light dispersion on the ceiling.

Installation

On a three-phase/DALI electrified track

Colour

Black (04) | Black / White (47)

Weight (Kg)

1.06

Mounting

dali track|three circuit track


Wiring

Product complete with DALI dimmable components, housed in a semi-hidden box on the track.

Complies with EN60598-1 and pertinent regulations



IP20



Technical data

Im system:	1845	MacAdam Step:	2
W system:	20.5	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Im source:	2170	Lamp code:	LED
W source:	18	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	90	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	85	Inrush current:	5 A / 50 µs
Beam angle [°]:	14°	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 31 luminaires B16A: 50 luminaires C10A: 52 luminaires C16A: 85 luminaires
CRI (minimum):	90	Overvoltage protection:	4kV Common mode & 2kV Differential mode
Colour temperature [K]:	3000	Control:	DALI-2

Polar

Imax=20439 cd	Lux			
	h	d	Em	Emax
	2	0.5	3877	5110
	4	0.9	969	1277
	6	1.4	431	568
	8	1.8	242	319