



Last information update: January 2025

Product configuration: RL74.39

RL74.39: Ø 163 mm - warm white - INVERTER - UGR<19 - 29.4W 2709lm - 3500K - CRI 90 - White / Aluminium



Product code

RL74.39: Ø 163 mm - warm white - INVERTER - UGR<19 - 29.4W 2709lm - 3500K - CRI 90 - White / Aluminium

Technical description

Round fixed luminaire designed to use LED lamps with C.o.B. technology. Version with rim for surface-mounting. Reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Dissipater made of painted grey die-cast aluminium. Product complete with LED lamp in warm white colour tone (3500K). Light beam with UGR<19 L<3000 cd/m² ideal for environments with video terminals. Luminaire complete with inverter for safety light.

Installation

Recessed using torsion springs which allow easy installation in false ceilings with thicknesses ranging from 1 mm to 20 mm.

Colour

White / Aluminium (39)

Weight (Kg)

1.13


Mounting

ceiling surface

Wiring

product complete with INVERTER


Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	2709	MacAdam Step:	2
W system:	29.4	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Im source:	3150	Lamp code:	LED
W source:	21	Number of lamps for optical assembly:	1
Luminous efficiency (Im/W, real value):	92.1	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	86	Inrush current:	19.4 A / 250 µs
CRI (minimum):	90	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 13 luminaires B16A: 21 luminaires C10A: 21 luminaires C16A: 35 luminaires
Colour temperature [K]:	3500	Overvoltage protection:	2kV Common mode & 1kV Differential mode


Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	76	71	68	66	71	68	67	64	75
1.0	79	76	73	70	75	72	72	69	80
1.5	84	81	79	77	80	78	77	74	87
2.0	87	85	83	81	84	82	81	79	91
2.5	89	87	86	84	86	84	84	81	94
3.0	90	89	88	87	87	86	85	83	96
4.0	91	90	89	89	88	88	87	84	98
5.0	91	91	90	90	89	89	87	85	99

Luminance curve limit



UGR diagram

Corrected UGR values (at 3150 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	17.9	18.5	18.1	18.7	19.0	17.9	18.5	18.1	18.7	19.0
	3H	17.7	18.3	18.0	18.6	18.9	17.7	18.3	18.0	18.6	18.9
	4H	17.7	18.2	18.0	18.5	18.8	17.7	18.2	18.0	18.5	18.8
	6H	17.6	18.1	17.9	18.4	18.7	17.6	18.1	17.9	18.4	18.7
	8H	17.5	18.0	17.9	18.3	18.7	17.5	18.0	17.9	18.3	18.7
	12H	17.5	18.0	17.9	18.3	18.6	17.5	18.0	17.9	18.3	18.6
4H	2H	17.7	18.2	18.0	18.5	18.8	17.7	18.2	18.0	18.5	18.8
	3H	17.5	18.0	17.9	18.3	18.6	17.5	18.0	17.9	18.3	18.6
	4H	17.4	17.8	17.8	18.2	18.6	17.4	17.8	17.8	18.2	18.6
	6H	17.3	17.7	17.8	18.1	18.5	17.3	17.7	17.8	18.1	18.5
	8H	17.3	17.6	17.7	18.0	18.4	17.3	17.6	17.7	18.0	18.4
	12H	17.2	17.5	17.7	17.9	18.4	17.2	17.5	17.7	17.9	18.4
8H	4H	17.3	17.6	17.7	18.0	18.4	17.3	17.6	17.7	18.0	18.4
	6H	17.2	17.4	17.7	17.9	18.4	17.2	17.4	17.7	17.9	18.4
	8H	17.1	17.4	17.6	17.8	18.3	17.1	17.4	17.6	17.8	18.3
	12H	17.1	17.3	17.6	17.8	18.3	17.1	17.3	17.6	17.8	18.3
12H	4H	17.2	17.5	17.7	17.9	18.4	17.2	17.5	17.7	17.9	18.4
	6H	17.1	17.4	17.6	17.8	18.3	17.1	17.4	17.6	17.8	18.3
	8H	17.1	17.3	17.6	17.8	18.3	17.1	17.3	17.6	17.8	18.3
Variations with the observer position at spacing:											
S =	1.0H	4.2 / -15.1					4.2 / -15.1				
	1.5H	7.0 / -37.3					7.0 / -37.3				
	2.0H	9.0 / -38.6					9.0 / -38.6				