

## View Opti Beam Lens round

Design iGuzzini /  
Arup

iGuzzini

Last information update: March 2025

### Product configuration: 451B

451B: round large body spotlight - spot



### Product code

451B: round large body spotlight - spot

### Technical description

Indoor adjustable spotlight with adapter for installation on a three-phase/DALI track. Device made of die-cast aluminium and a front part made of a thermoplastic material. Spotlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Optical assembly consisting of Warm White tone 3000K CRI97 LEDs with OPTIBEAM LENS technology and a well-defined spot light beam. Dimmable DALI driver built-in to box with a semi-hidden system on track. Option of installing a range of flat accessories including an OPTIBEAM REFRACTOR for varying light distribution, an elliptical distribution refractor, a louvre, a soft lens and an outdoor accessory like an asymmetric visor for eliminating stray light dispersion on the ceiling.

### Installation

On a three-phase/DALI electrified track

### Colour

Black (04) | Black / White (47)

### Weight (Kg)

1640


### Mounting

dali track|three circuit track

### Wiring

Product complete with DALI dimmable components, housed in a semi-hidden box on the track.

Complies with EN60598-1 and pertinent regulations



### Technical data

Im system:	2401	MacAdam Step:	2
W system:	28.3	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Im source:	2760	Lamp code:	LED
W source:	24	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	84.8	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	87	Inrush current:	5 A / 50 µs
Beam angle [°]:	16°	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 31 luminaires B16A: 50 luminaires C10A: 52 luminaires C16A: 85 luminaires
CRI (minimum):	97	Overvoltage protection:	4kV Common mode & 2kV Differential mode
Colour temperature [K]:	3000	Control:	DALI-2

### Polar

Imax=20110 cd	Lux			
	h	d	Em	E <sub>max</sub>
	2	0.6	3907	5027
	4	1.1	977	1257
	6	1.7	434	559
	8	2.2	244	314

$\alpha = 16^\circ$