

Front Light

Design iGuzzini


iGuzzini

Last information update: May 2024

Product configuration: N282+J005

N282: pendant - Warm White - Medium Optic

J005: Suspension L = 500 mm



Product code

N282: pendant - Warm White - Medium Optic **Attention! Code no longer in production**

Technical description

Pendant luminaire equipped with a three-phase adapter for electrified tracks, made of die-cast aluminium and thermoplastic material. The pendant system consists of steel cables L=2000 that provide a simple mechanical anchoring system. Having been rotated and tilted, the luminaire can be locked mechanically in position to ensure efficient light aiming (during maintenance operations too). Luminaire for high output C.O.B. technology LED lamp with monochrome emission in a warm white colour tone (3000K) CRI 90. Medium optic. Equipped with electronic ballast. Equipped with an accessory holding ring designed to contain a flat accessory. An external component may also be applied, such as directional flaps with 360° rotation.

Installation

On an electrified track

Colour

White (01) | Black (04)

Weight (Kg)

2.4

Mounting

three circuit track pendant|ceiling surface

Wiring

product complete with electronic components

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	4180	CRI:	90
W system:	44.1	Colour temperature [K]:	3000
Im source:	5300	MacAdam Step:	2
W source:	41	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	94.8	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	79	Number of optical assemblies:	1
Beam angle [°]:	16°		


Polar

	CIE nL 0.79 99-100-100-100-79 UGR <10-10				Lux			
	DIN A.61				h	d	Em	E _{max}
	UTE 0.79A+0.00T F*1=993 F*1+F*2=998 F*1+F*2+F*3=1000				2	0.6	5912	7363
	CIBSE LG3 L<1500 cd/m² at 65° UGR<10 L<1500 cd/mq @65°				4	1.1	1478	1841
					6	1.7	657	818
					8	2.2	370	460

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	71	67	65	63	67	64	64	62	78
1.0	74	71	68	67	70	68	68	65	83
1.5	78	75	73	72	74	73	72	70	88
2.0	80	78	77	76	77	76	75	73	93
2.5	82	80	79	78	79	78	77	75	96
3.0	83	82	81	80	81	80	79	77	98
4.0	84	83	83	82	82	81	80	78	99
5.0	84	84	83	83	82	82	81	79	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 5300 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise				
2H	2H	4.5	6.6	4.9	6.9	7.2	4.5	6.6	4.9	6.9	7.2
	3H	4.7	6.2	5.0	6.5	6.9	4.5	6.0	4.8	6.3	6.6
	4H	4.8	6.0	5.1	6.4	6.7	4.4	5.7	4.8	6.0	6.4
	6H	4.9	5.9	5.3	6.2	6.5	4.4	5.4	4.8	5.7	6.1
	8H	4.9	5.9	5.3	6.2	6.6	4.4	5.4	4.8	5.7	6.1
	12H	4.9	5.9	5.3	6.3	6.7	4.3	5.4	4.7	5.7	6.1
4H	2H	4.4	5.7	4.8	6.0	6.4	4.8	6.0	5.1	6.4	6.7
	3H	4.7	5.7	5.1	6.1	6.5	4.8	5.9	5.2	6.2	6.6
	4H	4.8	5.9	5.2	6.3	6.7	4.8	5.9	5.2	6.3	6.7
	6H	4.7	6.4	5.2	6.9	7.3	4.6	6.3	5.0	6.7	7.2
	8H	4.7	6.6	5.2	7.1	7.6	4.5	6.4	5.0	6.8	7.3
	12H	4.7	6.6	5.2	7.1	7.6	4.4	6.3	4.9	6.8	7.3
8H	4H	4.5	6.4	5.0	6.8	7.3	4.7	6.6	5.2	7.1	7.6
	6H	4.7	6.4	5.2	6.9	7.5	4.8	6.5	5.3	7.0	7.5
	8H	4.9	6.4	5.4	6.9	7.4	4.9	6.4	5.4	6.9	7.4
	12H	5.2	6.1	5.7	6.6	7.1	5.1	6.0	5.6	6.5	7.0
12H	4H	4.4	6.3	4.9	6.8	7.3	4.7	6.6	5.2	7.1	7.6
	6H	4.7	6.2	5.3	6.7	7.3	4.9	6.4	5.4	6.9	7.4
	8H	5.1	6.0	5.6	6.5	7.0	5.2	6.1	5.7	6.6	7.1
Variations with the observer position at spacing:											
S =	1.0H	4.0 / -2.8					4.0 / -2.8				
	1.5H	6.5 / -3.0					6.5 / -3.0				
	2.0H	8.4 / -3.1					8.4 / -3.1				