


Last information update: February 2025

Product configuration: RF67.01

RF67.01: Pendant Tecnica Evo - Ø92 body - DALI - 27.5W 3384lm - 3000K - White

**Product code**

RF67.01: Pendant Tecnica Evo - Ø92 body - DALI - 27.5W 3384lm - 3000K - White

Technical description

Pendant luminaire fitted with an adapter for installation on an electrified DALI track. High yield LED lamp. Die-cast aluminium luminaire. Optical system with high performance P.V.D. (Physical Vapour Deposition) anti-scratch aluminium reflector that offers an excellent light efficiency ratio. Balanced pendant system with double steel cable and adjustment system. Fitted with mechanical aiming locks, so rotation and tilting movements can be locked in position to ensure efficient light aiming even after the original installation or during maintenance. Integrated DALI dimmable power supply unit. Designed to house other optical accessories in the range. Interchangeable reflectors are available, which allow the emission angle to be varied as required, even after the original installation.

Installation

Installation on an electrified track.

Colour

White (01)

Weight (Kg)

1.46

Mounting

dali track

Wiring


Built-in DALI dimmable power supply.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	3384	CRI (minimum):	80
W system:	27.5	Colour temperature [K]:	3000
lm source:	3600	MacAdam Step:	2
W source:	24	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	123.1	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	94	Number of optical assemblies:	1
Beam angle [°]:	56°	Control:	DALI-2


Polar

	Imax=4428 cd	C0-180	CIE			
	90°	180°	nL 0.94	Lux		
	90°	90°	88-100-100-100-94	h	d1	d2
	5000	0°	UGR 19.4-17.6	Em	Emax	
	α=56°		DIN A.61	2	2.1	2.1
UTE 0.94A+0.00T				4	4.3	4.3
F*1=980				6	6.4	6.4
F*1+F*2=999				8	8.5	8.5
F*1+F*2+F*3=1000						
CIBSE LG3 L<3000 cd/m² at 65°						

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	84	80	76	74	79	76	75	72	77
1.0	88	84	81	79	83	80	80	77	82
1.5	93	89	87	85	88	86	85	83	88
2.0	95	93	91	90	92	90	89	87	92
2.5	97	96	94	93	94	93	92	89	95
3.0	99	97	96	95	96	95	94	91	97
4.0	100	99	98	97	97	97	95	93	99
5.0	100	100	99	99	98	98	96	94	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 3000 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		viewed crosswise					viewed endwise				
		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
2H	2H	19.9	20.5	20.2	20.8	21.0	18.2	18.8	18.5	19.0	19.2
	3H	19.8	20.3	20.1	20.6	20.9	18.1	18.6	18.4	18.9	19.1
	4H	19.7	20.2	20.1	20.5	20.8	18.0	18.5	18.3	18.8	19.1
	6H	19.6	20.1	20.0	20.4	20.7	17.9	18.4	18.3	18.7	19.0
	8H	19.6	20.1	20.0	20.4	20.7	17.9	18.3	18.2	18.6	19.0
	12H	19.6	20.0	19.9	20.3	20.7	17.8	18.3	18.2	18.6	18.9
4H	2H	19.7	20.2	20.1	20.5	20.8	18.0	18.5	18.3	18.8	19.1
	3H	19.6	20.0	20.0	20.3	20.7	17.8	18.3	18.2	18.6	19.0
	4H	19.5	19.9	19.9	20.2	20.6	17.8	18.1	18.2	18.5	18.9
	6H	19.4	19.7	19.8	20.1	20.5	17.7	18.0	18.1	18.4	18.8
	8H	19.4	19.7	19.8	20.1	20.5	17.6	17.9	18.1	18.3	18.8
	12H	19.3	19.6	19.8	20.0	20.5	17.6	17.8	18.0	18.3	18.7
8H	4H	19.4	19.7	19.8	20.1	20.5	17.6	17.9	18.1	18.3	18.8
	6H	19.3	19.5	19.7	20.0	20.4	17.5	17.8	18.0	18.2	18.7
	8H	19.2	19.4	19.7	19.9	20.4	17.5	17.7	18.0	18.1	18.6
	12H	19.2	19.3	19.7	19.8	20.3	17.4	17.6	17.9	18.1	18.6
12H	4H	19.3	19.6	19.8	20.0	20.5	17.6	17.8	18.0	18.3	18.7
	6H	19.2	19.4	19.7	19.9	20.4	17.5	17.7	18.0	18.1	18.6
	8H	19.2	19.3	19.7	19.8	20.3	17.4	17.6	17.9	18.1	18.6
Variations with the observer position at spacing:											
S =	1.0H	5.6 / -12.7					5.8 / -14.2				
	1.5H	8.4 / -17.1					8.6 / -16.7				
	2.0H	10.4 / -19.3					10.6 / -18.3				