


Last information update: November 2024



Accessory code

PE06: Power supply base with suspension cables - Ceiling-mounted luminaire - Ø234 UP-DOWN - General Light

Technical description

Base unit for pendant/planned power supply of the structure - surface version. Shaped steel plate for coupling to the ceiling - polycarbonate covering rosette. The pre-arranged wires - L 2,500 mm - simultaneously act as suspension and power supply - the adjustment to the length and the wiring is done in the upper section of the light unit, complete with connection terminal board and safety cable clamps. Sliding devices, to be positioned along the length of the cables, allow the pendant to be aesthetically shaped. 2 DALI power supply drivers included.

Installation

steel plate for coupling onto the laying surface with screws and anchors (not included)

Colour

White (01) | Black (04)

Weight (Kg)

0.63

Wiring

connection to the network with rapid coupling terminal board positioned on the base unit plate - 2 power supply drivers included with integrated wiring. Adjustment of the power supply/pendant cables and further wiring to be done on the upper section of the light unit, arranged with connecting terminal board and safety cable clamps.

Complies with EN60598-1 and pertinent regulations



IP40

Technical data

Power factor: See installation instructions

Inrush current: 18 A / 250 µs

Maximum number of
luminaires of this type per
miniature circuit breaker:

B10A:	21 luminaires
B16A:	34 luminaires
C10A:	35 luminaires
C16A:	57 luminaires

Minimum dimming %:

1

Overvoltage protection:

2kV Common mode & 1kV
Differential mode

Control:

DALI-2