

## View Opti Beam Lens square

Design iGuzzini /  
Arup

iGuzzini

Last information update: May 2024

### Product configuration: Q340

Q340: square large body spotlight - WW



### Product code

Q340: square large body spotlight - WW **Attention! Code no longer in production**

### Technical description

Indoor adjustable spotlight with adapter for installation on a three-phase/DALI track. Device made of die-cast aluminium and a front part made of a thermoplastic material. Spotlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Optical assembly consisting of Neutral White tone 4000K LEDs with OPTIBEAM LENS technology and wall-washer light distribution for homogeneous vertical wall lighting. Dimmable electronic driver built-in to box with a semi-hidden system on track. Option of installing a range of flat accessories including an OPTIBEAM REFRACTOR for varying light distribution, a louver, a soft lens and an outdoor accessory like an asymmetric visor for eliminating stray light dispersion on the ceiling.

### Installation

On a three-phase/DALI electrified track

### Colour

Black (04) | Black / White (47)

### Weight (Kg)

1.85


### Mounting

dali track|three circuit track

### Wiring

Product complete with dimmable electronic components, housed in a semi-hidden box on the track.


Complies with EN60598-1 and pertinent regulations



### Technical data

Im system:	2485	Colour temperature [K]:	4000
W system:	29	MacAdam Step:	2
Im source:	3600	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
W source:	24	Lamp code:	LED
Luminous efficiency (Im/W, real value):	85.7	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	69	Control:	Push Dim
CRI (minimum):	80		

Polar



Illuminances

Lux						Wall distance = 1m					
3											
	0.4	0.9	3	9	27	48	27	9	3	0.9	0.4
2	1	3	7	20	54	92	54	20	7	3	1
	2	4	10	31	95	165	95	31	10	4	2
1	3	5	13	46	136	220	136	46	13	5	3
	3	7	19	57	129	187	129	57	19	7	3
0											
	m	-2	-1	0	1	2	3				