## iGuzzini

Last information update: June 2024

#### Accessory code

X846: 200W DALI dimmable power supply - Vin 220-240Vac 50/60Hz

### Technical description



#### Installation

Fitted with flaps with through-holes and slots for installation. To install the power supply units inside poles with twin access covers, the accessory code X743 must be used that needs to be ordered separately. - For outdoor installations, the power supply must be inserted in a protective box; - the IP rating requires the installer to use a suitable protective box; - iGuzzini guarantees an IP66 rating when used with one of the accessories indicated in the luminaire instruction sheet.

<b>Colour</b> Indeterminate (00)	<b>Weight (Kg)</b> 3.51	Dimension (mm) (*) 188x67.5x36.5
		* The dimensions may change according to production requirements
		to ensure that performance levels and installation methods are
		observed.

# Wiring

The power supply is fitted with 3 exit cables; input / DALI / luminaire output. Input cable length L= 600 mm, luminaire output L= 180 mm, DALI L= 235 mm.

#### Notes

For information regarding the MINIMUM and MAXIMUM number of products that can be connected refer to the luminaire instruction sheet. 1 address, 1 DALI load (2 mA)

Complies with EN60598-1 and pertinent regulations



Technical data			
Current out [mA]:	400	Control:	DALI-2