


Ultimo aggiornamento delle informazioni: Ottobre 2024

Configurazione di prodotto: BQ21

BQ21: Wall-/Ceiling-mounted - 12 Wram White LEDs - 24V dc - L=1056mm - Wall Grazing Optic

**Codice prodotto**

BQ21: Wall-/Ceiling-mounted - 12 Wram White LEDs - 24V dc - L=1056mm - Wall Grazing Optic

Descrizione tecnica

Direct light luminaire, designed to use monochrome LED lamps. Ceiling- and wall-mounted. Consists of a body and supports for installation (to be ordered separately). Extruded aluminium body, with zamak die-cast end caps complete with silicone seals. Coated with liquid acrylic paint with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED power plate in Wram White 2700K with 24V dc electronic circuit (ballast to be ordered separately); 24V smart driver allowing constant light flow emission despite variations in the input voltage (from 30V dc to 16V dc). Fitted with a PMMA diffusing filter and optic with plastic (methacrylate) lens for Wall Grazing lighting. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN 60598-1 standards and particular requirements.

Installazione

The following accessories are available for installation: adjustable wall-mounted arms in AISI304 stainless steel (L=83mm code BZJ9, 200mm code BZJ8) and a plate for surface- or ceiling-mounting made of anodised aluminium (BZJ7).

Colore

Grigio (15)

Peso (Kg)

1.59

Montaggio

a parete/a soffitto

Cablaggio

The product is supplied with a single nickel-plated brass cable gland PG9 and a 2x1mm² PVC and polyurethane outlet cable, 2000mm long. For the electrical connection there is an IP68 linear connector (BZK6) and an IP66 junction box with quick-coupling terminals (BZK7). 24V dc electronic ballasts to be ordered separately: 120W (BZK0), 240W (9912) and 480W (BZK1)

Note

Product complete with LED lamp.

Soddisfa EN60598-1 e relative note



IK05

IP66




EAC

**Dati tecnici**

Im di sistema:	514	Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)
W di sistema:	14	Life Time LED 2:	66,000h - L80 - B10 (Ta 40°C)
Im di sorgente:	950	Voltaggio [Vin]:	24
W di sorgente:	13	Codice lampada:	LED
Efficienza luminosa (lm/W, dati di sistema):	36.7	Numero di lampade per vano ottico:	1
Im in modalità emergenza:	-	Codice ZVEI:	LED
Flusso totale emesso a 90° o superiore [Lm]:	0	Numero di vani ottici:	1
Light Output Ratio (L.O.R.) [%]:	54	Intervallo temperatura ambiente operativa:	da -30°C a 50°C.
CRI (minimo):	80	Corrente LED [mA]:	350
Temperatura colore [K]:	2700	Control:	PWM
MacAdam Step:	3		

Polare



Illuminanti

Lux													Wall distance = 1m	
3														
	0.1	0.1	0.4	1	3	4	3	1	0.5	0.2	0.1			
2	0.4	0.9	2	4	7	9	8	4	2	1	0.6			
	0.8	1	3	5	8	11	10	6	3	2	1.0			
1	1	2	3	6	9	11	10	6	3	2	1			
	1	2	3	5	8	10	9	6	4	2	1			
0														
	m	-2	-1	0	1	2	3							