


Last information update: February 2025

**Product configuration: 319A**

319A: SIPARIO Ø86 spotlight - DALI - Flood - OBLens -

**Product code**

319A: SIPARIO Ø86 spotlight - DALI - Flood - OBLens -

**Technical description**

Ø86 adjustable spotlight with adapter for installation on a base or electrified track. LED lamp with C.O.B. (Chip on board) technology, -CRI90- high colour rendering and 3000K tone.

Die-cast aluminium body with thermoplastic rear cap and front ring (Mass-Balance). The product can be rotated by 360° around the vertical axis with a mechanical lock and tilted by 90° relative to the horizontal plane. Passive heat dissipation.

OptiBeam Lens optical system with Flood optic.

Dimmable electronic DALI-2 power supply integrated in the body of the luminaire.

Spotlight with Push&Go system designed to facilitate and safely accelerate the connection between product and optic accessory.

Mechanically disconnecting the accessory allows it to be disengaged but not dropped. Three internal accessories and one external one can be used simultaneously. All internal accessories rotate 360° about the spotlight longitudinal axis.

**Installation**

Base or mains voltage track.

**Colour**

White (01) | Matte black (V0)

**Weight (Kg)**

0.87

**Mounting**


three circuit track

Complies with EN60598-1 and pertinent regulations


**Technical data**

lm system:	1599	CRI (minimum):	90
W system:	18	Colour temperature [K]:	3000
lm source:	1950	MacAdam Step:	2
W source:	16	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	88.8	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	82	Number of optical assemblies:	1
Beam angle [°]:	28°	Control:	DALI-2

**Polar**

Imax=5863 cd		Lux			
90°	180°	h	d	Em	Emax
		2	1	1166	1466
		4	2	291	366
		6	3	130	163
		8	4.1	73	92
	α=28°				

### Isolux



### UGR diagram

Corrected UGR values (at 1950 lm bare lamp luminous flux)												
Riflect.:		viewed crosswise					viewed endwise					
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30	
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30	
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	
Room dim		viewed crosswise					viewed endwise					
x	y											
2H	2H	11.0	13.0	11.4	13.3	13.7	11.0	13.0	11.4	13.3	13.7	
	3H	10.9	12.5	11.3	12.8	13.1	10.9	12.5	11.3	12.8	13.1	
	4H	10.8	12.2	11.2	12.5	12.8	10.8	12.2	11.2	12.5	12.8	
	6H	10.8	11.8	11.1	12.2	12.5	10.8	11.9	11.2	12.2	12.6	
	8H	10.7	11.8	11.1	12.1	12.5	10.7	11.8	11.1	12.1	12.5	
	12H	10.7	11.7	11.1	12.1	12.4	10.7	11.7	11.1	12.1	12.5	
4H	2H	10.8	12.2	11.2	12.5	12.8	10.8	12.2	11.2	12.5	12.8	
	3H	10.7	11.8	11.1	12.1	12.5	10.7	11.8	11.1	12.1	12.5	
	4H	10.6	11.6	11.1	12.0	12.4	10.6	11.6	11.1	12.0	12.4	
	6H	10.3	11.9	10.8	12.3	12.8	10.3	11.9	10.8	12.3	12.8	
	8H	10.1	11.9	10.6	12.4	12.9	10.2	11.9	10.6	12.4	12.9	
	12H	10.0	11.9	10.5	12.4	12.9	10.0	11.9	10.5	12.4	12.9	
8H	4H	10.2	11.9	10.6	12.4	12.9	10.1	11.9	10.6	12.4	12.9	
	6H	10.0	11.8	10.5	12.2	12.8	10.0	11.8	10.5	12.2	12.8	
	8H	10.0	11.5	10.5	12.0	12.6	10.0	11.5	10.5	12.0	12.6	
	12H	10.1	11.2	10.6	11.7	12.2	10.1	11.2	10.6	11.7	12.2	
12H	4H	10.0	11.9	10.5	12.4	12.9	10.0	11.9	10.5	12.4	12.9	
	6H	10.0	11.5	10.5	12.0	12.6	10.0	11.5	10.5	12.0	12.6	
	8H	10.1	11.2	10.6	11.7	12.2	10.1	11.2	10.6	11.7	12.2	
Variations with the observer position at spacing:												
S =		1.0H	4.5 / -7.0				4.5 / -7.0					
		1.5H	7.2 / -10.2				7.2 / -10.2					
		2.0H	9.2 / -12.9				9.2 / -12.9					