

Last information update: April 2025

**Product configuration: MM97**

MM97: Fixed round recessed luminaire - Ø212 mm - neutral white - wide flood optic

**Product code**MM97: Fixed round recessed luminaire - Ø212 mm - neutral white - wide flood optic **Attention! Code no longer in production****Technical description**

Fixed round luminaire designed to use a LED lamp with C.O.B. technology. Version with rim for surface-mounting. Reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Die-cast aluminium body and passive dissipation system. Product complete with LED lamp in neutral white colour tone (4,000K). General light emission, with controlled luminance  $UGR < 19$   $1500 \text{ cd/m}^2$   $\alpha > 65^\circ$  wide flood optic.

**Installation**

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 25 mm

**Colour**

White / Aluminium (39)

**Weight (Kg)**

2.03

**Mounting**

ceiling recessed

**Wiring**

Product complete with electronic components


Complies with EN60598-1 and pertinent regulations



IP20

IP54

On the visible part of the product once installed

**Technical data**

lm system:	4426	CRI (minimum):	80
W system:	35.4	Colour temperature [K]:	4000
lm source:	5150	MacAdam Step:	2
W source:	31	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	125	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	86	Number of optical assemblies:	1
Beam angle [°]:	56°		


**Polar**

	<b>Imax=5218 cd</b> 90° 180° 90° 4500 0° $\alpha = 56^\circ$				<b>CIE</b> nL 0.86 95-100-100-100-86 UGR 17.8-17.8 <b>DIN</b> A.61 <b>UTE</b> 0.86A+0.00T F*1=946 F*1.4F*2=1000 F*1.4F*2+F*3=1000 <b>CIBSE</b> LG3 L<1500 cd/m <sup>2</sup> at 65° UGR<19   L<1500 cd/mq @65°				<b>Lux</b> h d Em Emax 2 2.1 971 1304 4 4.3 243 326 6 6.4 108 145 8 8.5 61 82			

# Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	76	71	68	65	70	67	67	64	74
1.0	79	75	72	70	74	72	71	68	80
1.5	84	81	79	77	80	78	77	74	86
2.0	87	85	83	81	83	82	81	78	91
2.5	89	87	85	84	86	84	83	81	94
3.0	90	88	87	86	87	86	85	83	96
4.0	91	90	89	88	88	88	86	84	98
5.0	91	91	90	90	89	89	87	85	99

# Luminance curve limit



# UGR diagram

Corrected UGR values (at 5150 lm bare lamp luminous flux)											
Reflect.: ceiling walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	18.4	19.1	18.7	19.3	19.6	18.4	19.1	18.7	19.3	19.6
	3H	18.3	18.9	18.6	19.1	19.4	18.3	18.9	18.6	19.1	19.4
	4H	18.2	18.8	18.5	19.0	19.3	18.2	18.8	18.5	19.0	19.3
	6H	18.1	18.6	18.5	18.9	19.3	18.1	18.6	18.5	18.9	19.3
	8H	18.1	18.6	18.4	18.9	19.2	18.1	18.6	18.4	18.9	19.2
	12H	18.0	18.5	18.4	18.8	19.2	18.0	18.5	18.4	18.8	19.2
4H	2H	18.2	18.8	18.5	19.0	19.3	18.2	18.8	18.5	19.0	19.3
	3H	18.0	18.5	18.4	18.8	19.2	18.0	18.5	18.4	18.8	19.2
	4H	17.9	18.4	18.3	18.7	19.1	17.9	18.4	18.3	18.7	19.1
	6H	17.9	18.2	18.3	18.6	19.0	17.9	18.2	18.3	18.6	19.0
	8H	17.8	18.1	18.3	18.6	19.0	17.8	18.1	18.3	18.6	19.0
	12H	17.8	18.1	18.2	18.5	19.0	17.8	18.1	18.2	18.5	19.0
8H	4H	17.8	18.1	18.3	18.6	19.0	17.8	18.1	18.3	18.6	19.0
	6H	17.7	18.0	18.2	18.4	18.9	17.7	18.0	18.2	18.4	18.9
	8H	17.7	17.9	18.2	18.4	18.9	17.7	17.9	18.2	18.4	18.9
	12H	17.6	17.8	18.1	18.3	18.8	17.6	17.8	18.1	18.3	18.8
12H	4H	17.8	18.1	18.2	18.5	19.0	17.8	18.1	18.2	18.5	19.0
	6H	17.7	17.9	18.2	18.4	18.9	17.7	17.9	18.2	18.4	18.9
	8H	17.6	17.8	18.1	18.3	18.8	17.6	17.8	18.1	18.3	18.8
Variations with the observer position at spacing:											
S =	1.0H	4.5 / -24.2					4.5 / -24.2				
	1.5H	7.2 / -33.8					7.2 / -33.8				
	2.0H	9.2 / -34.2					9.2 / -34.2				