


THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

## ROUGH INSTALLATION



- A- ADD BX CABLE (**BY OTHERS**). FOR 0-10V DIMMING ADD. BX CABLE AND CONNECTOR (**BY OTHERS**).  
 B- ENGAGE HANGER BARS (4X, **PROVIDED**) IN SLOTS AVAILABLE, CONNECT THEM TOGETHER.  
 C- FASTEN HANGER BARS TO CEILING STRUCTURE WITH APPROPRIATE SCREWS (**BY OTHERS**).



## INSULATION / JUNCTION BOX

### BOX DIMENSIONS

|                | BOX DIMS ( A x B* x C* x F )                                     | CUT OUT ( D x E )           |
|----------------|--|-----------------------------|
| BI5125/BI5125A | 5 7/8" X 11 19/32" X 4 9/16" X 5 1/4"<br>149mmX294mmX116mmX134mm | 1-1/2"x5-1/2"<br>37mmx141mm |




\*B- DIMENSION INCLUDES MOUNTING BRACKETS.  
 \*C- CLEARANCE HEIGHT NEEDED FOR INSTALLATION

HANGER BARS DIMENSIONS - 12 3/4" to 23 3/4" (324mm x 600mm)

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

## FINISH INSTALLATION

- A- CONNECT THE POWER SUPPLY TO THE BRANCH CIRCUIT WITH MARRETES AND CONNECTOR. SECURE WITH ZIP TIES.  
( see connections on page3)  
B- PLACE SCREWDRIVER IN ALLOCATED POSITION AND FASTEN THE POWER SUPPLY TO THE TOP OF  
THE INSULATION BOX. TIGHTEN POWER SUPPLY IN THE ALIGNMENT BRACKET.  
C- LIFT AND HOLD THE CLIPS AND PLACE INTO THE CUT-OUT.



## SPECIFICATIONS

### MODELS

#### DOWNLIGHT

I.MK49 - 10W, 4000K LED, FLOOD, 95CRI  
I.P473 - 10W, 3500K LED, SPOT, 95CRI  
I.P474 - 10W, 3500K LED, MEDIUM, 95CRI  
I.P475 - 10W, 3500K LED, FLOOD, 95CRI  
I.P129 - 10W, 3000K LED, SPOT, 90CRI  
I.MK50 - 10W, 3000K LED, MEDIUM, 90CRI  
I.MK51 - 10W, 3000K LED, FLOOD, 90CRI  
I.P130 - 10W, 3000K LED, SPOT, 97CRI  
I.MQ80 - 10W, 3000K LED, MEDIUM, 95CRI  
I.MQ81 - 10W, 3000K LED, FLOOD, 97CRI  
I.P131 - 10W, 2700K LED, MEDIUM, 95CRI  
I.MM77 - 10W, 2700K LED, MEDIUM, 95CRI  
I.MM78 - 10W, 2700K LED, FLOOD, 95CRI

#### GENERAL LIGHT

I.MQ55 - 10W, 4000K LED, GENERAL LIGHT, 95CRI  
I.MQ57 - 10W, 3000K LED, GENERAL LIGHT, 90CRI

#### WALL WASHER

I.MQ67 - 10W, 4000K LED, WALL WASHER, 95CRI  
I.P493 - 10W, 3500K LED, WALL WASHER, 95CRI  
I.MQ68 - 10W, 3000K LED, WALL WASHER, 90CRI  
I.P146 - 10W, 2700K LED, WALL WASHER, 96CRI

#### I.MXXX-XXX-XX-XX

MODEL VOLTAGE TRIM COLOUR DIM

**VOLTAGE:** UNV (120-277V)  
120V (120V ONLY)

**TRIM COLOUR:** 01 (WHITE)  
10 (GRAY)

**DIM:** D10 (0-10V DIMMING)  
LTE (LEADING/TRIAC DIMMING)

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

### CONNECTIONS

