


Last information update: June 2023

Product configuration: E195

E195: Outer applique. A diffused-light, wall-mounted fixture.

**Product code**E195: Outer applique. A diffused-light, wall-mounted fixture. **Attention! Code no longer in production****Technical description**

A diffused-light fixture designed for use with mains voltage warm white LED light sources. Comprised of a coated extruded aluminium body, a polycarbonate screen and a plastic top cover. The product is anchored to the wall using a fastening plate made from die-cast aluminium alloy. The diffuser screen is made from polycarbonate, with a top cover made from coated plastic. It is locked into place by a thread and safety bolt. The screen is secured to the extruded body by a die-cast element that houses the mains-voltage LED. The product is secured to the wall by anchoring plugs provided with the product. All external screws are made of A2 stainless steel.

Installation

Secured to the wall by anchoring plugs provided with the product.

Colour

Grey (15)

Weight (Kg)

0.8


Mounting

wall arm|ground surface|wall surface

Wiring

Complete with mains-voltage LED. Electrical connection via connectors.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	276	Colour temperature [K]:	3000
W system:	7.6	MacAdam Step:	3
lm source:	600	Life Time LED 1:	30,000h - L80 (Ta 25°C)
W source:	7.6	Ballast losses [W]:	0
Luminous efficiency (lm/W, real value):	36.3	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	138	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	46	Number of optical assemblies:	1
CRI (minimum):	80	Intervallo temperatura ambiente:	from -20°C to +35°C. (*)

* Preliminary data

Polar

Imax=53 cd C0-180 γ=62°		Lux				
		h	d1	d2	Em	Emax
	180°	1	-	-	10	30
	90°	2	-	-	3	8
	60°	3	-	-	1	3
	0°	4	-	-	0.6	2

Isolux

