


Palco Recessed / Surface

Last information update: April 2024

**Product configuration: QC26**  
QC26: Palco single recess Ø51 - spot - remote driver



**Product code**  
QC26: Palco single recess Ø51 - spot - remote driver

**Technical description**  
Miniaturised adjustable spotlight for recessed installation. Spotlight body with a die-cast aluminium dissipation system - cast zamak rotation unit - machined aluminium recess base - steel wire fixing springs. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.

**Installation**  
Recessed base with surface stop plate - steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole Ø36 mm.


<b>Colour</b>	<b>Weight (Kg)</b>
White (01)   Black (04)	0.3

**Mounting**  
wall recessed|ceiling recessed

**Wiring**  
Output cables for connecting to power supply line.

**Notes**  
Technical and anti-glare accessories available.

Complies with EN60598-1 and pertinent regulations



**Technical data**

Im system:	949	CRI (minimum):	90
W system:	15	Colour temperature [K]:	3000
Im source:	1460	MacAdam Step:	2
W source:	15	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	63.3	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	65	Number of optical assemblies:	1
Beam angle [°]:	14°	LED current [mA]:	400

**Polar**

