

## Palco Recessed / Surface



Design Artec  
Studio

iGuzzini

Last information update: October 2024

### Product configuration: QC26

QC26: Palco single recess Ø51 - spot - remote driver



### Product code

QC26: Palco single recess Ø51 - spot - remote driver

### Technical description

Miniaturised adjustable spotlight for recessed installation. Spotlight body with a die-cast aluminium dissipation system - cast zamak rotation unit - machined aluminium recess base - steel wire fixing springs. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.

### Installation

Recessed base with surface stop plate - steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole Ø36 mm.

### Colour

White (01) | Black (04)

### Weight (Kg)

0.3

### Mounting

wall recessed|ceiling recessed

### Wiring

Output cables for connecting to power supply line.

### Notes

Technical and anti-glare accessories available.

Complies with EN60598-1 and pertinent regulations



### Technical data

Im system:	949	CRI (minimum):	90
W system:	15	Colour temperature [K]:	3000
Im source:	1460	MacAdam Step:	2
W source:	15	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	63.3	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	65	Number of optical assemblies:	1
Beam angle [°]:	14°	LED current [mA]:	400

### Polar

Imax=8274 cd 90° 180° 90° 9000 0° α = 14°	C0-180		Lux		
	h	d1	d2	Em	Emax
	2	0.5	0.5	1640	2069
	4	1	1	410	517
	6	1.5	1.5	182	230
	8	2	2	102	129