


Last information update: May 2024

Product configuration: BE58+L338

BE58: Ceiling-mounted recessed luminaire with IP66 protection rating, large body, 150W HIT G12 adjustable Spot

**Product code**BE58: Ceiling-mounted recessed luminaire with IP66 protection rating, large body, 150W HIT G12 adjustable Spot **Attention! Code no longer in production****Technical description**

Downlighter with HIT metal halide lamps with adjustable Spot optic. Consists of a round optical assembly, frame, lateral component holder box and an outer casing to be ordered separately where necessary. The optical assembly and frame are made of aluminium alloy, coated with liquid acrylic paint with a high level of weather and UV ray resistance. The tempered sodium - calcium sealing glass is transparent, with customised serigraphy on the edge, 5mm thick, joined to the frame with silicone. Reflectors made of 99.96% super-pure aluminium, fixed to the assembly by quick-coupling springs. Adjustable optic: $\pm 20^\circ$ about the vertical axis and 180° relative to the horizontal plane. Adjustable versions have a system for aiming the optic using a tool even when the lamp is on (without the risk of burns). Complete with a black-painted aluminium multi-groove ring. The lateral component holder box and top end cap are made of black-painted aluminium alloy, complete with a silicone internal seal to guarantee watertightness. The optical assembly and separate lateral box are connected by stainless steel threaded connectors with rubber cable glands for a watertight seal and armoured cable L=500mm. Set up for pass-through wiring using two M24x1.5 nickel-plated brass cable glands, suitable for cables with diameter 7 - 16mm. Ceiling-mounting system consists of special A2 stainless steel screws complete with black aluminium alloy and plastic coupling supports. There is a single tool (No. 3 Allen key) for opening the frame, the lateral box cap and for the fixing system. The outer casing for concrete ceilings is made of black-painted ready-galvanised sheet aluminium complete with an end cap and threaded bar.

Installation

Recessed in false ceilings 5 - 60mm thick. Hole for preparation of false ceiling $\varnothing=212\text{mm}$. Installed on concrete ceilings using an outer casing, to be ordered separately.

Colour

Grey (15)

Mounting

ceiling surface

Wiring

Luminaire equipped with electromagnetic ballast

Notes

Plastic adapter disk available for flush-mounting the frame on ceilings made of concrete exposed to view (can only be used with the product with aluminium frame, without the stainless cover). Products set up for installation of a stainless steel safety kit L=2000mm.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	8865	CRI:	96
W system:	170	Colour temperature [K]:	4200
Im source:	14500	Lamp code:	L338
W source:	150	Socket:	G12
Luminous efficiency (Im/W, real value):	52.1	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	HIT-CE
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	61	Intervallum temperatura ambiente:	from -20°C to $+35^\circ\text{C}$.
Beam angle $[\alpha]$:	12°		

Polar

Imax=101503 cd		Lux			
		h	d	Em	Emax
	90°	2	0.4	19800	25376
	180°	4	0.8	4950	6344
	90°	6	1.3	2200	2820
	0°	8	1.7	1238	1586
$\alpha = 12^\circ$					

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	53	50	47	45	49	47	47	44	72
1.0	56	53	51	49	52	50	50	48	78
1.5	59	57	55	54	56	55	54	52	85
2.0	61	60	58	57	59	58	57	55	90
2.5	63	61	60	59	60	60	59	57	93
3.0	64	63	62	61	62	61	60	58	95
4.0	64	64	63	62	63	62	61	59	97
5.0	65	64	64	63	63	63	62	60	98

Luminance curve limit

