

Product configuration: QL72

QL72: Ø1157mm - Tunable White - Opal - DALI



QL72: Ø1157mm - Tunable White - Opal - DALI

Round luminaire for ceiling-mounted installation with option of recessed or pendant installation via an accessory to be ordered separately. Direct emission designed to use Tunable White 2700K+6500K LED lamps. The optical assembly consists of an extruded painted aluminum frame, a satin finish methacrylate diffuser screen for general light emission and a sheet metal rear closing base. The DALI DT8driver is housed in the upper part of the product.

Ceiling-mounted. Recessed or pendant-mounted using an accessory to be ordered separately.

Colour
White (01) | Black (04)

Weight (Kg)
20

mounting
wall surface|ceiling surface

Product complete with electronic components. The electrical cables used are made of a "halogen free" material. (This means that the cables do not contain any halogen materials that in the event of a fire do not emit toxic or corrosive gases and only a small quantity of opaque fumes).

Complies with EN60598-1 and pertinent regulations



Im system:	12240	CRI (minimum):	90
W system:	107.2	Colour temperature [K]:	Tunable white 2700 - 6500
Im source:	17000	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
W source:	96	Lamp code:	LED
Luminous efficiency (lm/W, real value):	114.2	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	72	Control:	DALI-2

I_{max}=4279 cd **C0-180** **CIE**
nL 0.72
47-78-95-100-72
UGR 21.4-20.9
DIN
A.41
UTE
0.72E+0.00T
F"1=469
F"1+F"2=784
F"1+F"2+F"3=954