Design iGuzzini

iGuzzini

Last information update: April 2025

Product configuration: Q242

Q242: extractable, adjustable, recessed LED luminaire - DALI control gear included



Product code

Q242: extractable, adjustable, recessed LED luminaire - DALI control gear included

Technical description

Extractable, adjustable, recessed luminaire for neutral white LED lamp. Passive heat dispersion system. Die-cast aluminium main body and frame; stainless steel rotation hinge. Rotation ring with safety cover in a high resistance thermoplastic material. Body adjusted with a manual manoeuvre device: internal 40° - external 65° - rotation on 355° axis. Reflector with high efficiency superpure aluminium optic - flood beam angle. Die-cast aluminium lamp body closure ring. Tempered transparent glass screen. Dimmerable DALI control gear supplied and connected to the luminaire.

Installation

recessed using steel springs in false ceilings with thicknesses starting at 1 mm

Weight (Kg) Colour White (01) 0.85



ø 136



Mounting

ceiling recessed

Wiring on control gear box with quick-coupling connections



Technical data						
Im system:	2525	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)			
W system:	23.5	Lamp code:	LED			
Im source:	3200	Number of lamps for optical	1			
W source:	21	assembly:				
Luminous efficiency (Im/W,	107.5	ZVEI Code:	LED			
real value):		Number of optical	1			
Im in emergency mode:	-	assemblies:				
Total light flux at or above	0	Power factor:	See installation instructions			
an angle of 90° [Lm]:		Inrush current:	18 A / 250 μs			
Light Output Ratio (L.O.R.)	79	Maximum number of				
[%]:		luminaires of this type per	B10A: 21 luminaires			
Beam angle [°]:	42°	miniature circuit breaker:	B16A: 34 luminaires			
CRI (minimum):	80		C10A: 35 luminaires			
Colour temperature [K]:	4000	Minimum dimension of	C16A: 57 luminaires			
MacAdam Step:	2	Minimum dimming %:				
·		Overvoltage protection:	2kV Common mode & 1kV Differential mode			
		Control:	DALI-2			


Polar

lmax=4343 cd	CIE	Lux			
90° 180° 90°	nL 0.79 97-100-100-100-79	h	d	Em	Emax
	UGR 20.4-20.4 DIN A.61	2	1.5	842	1086
	UTE 0.79A+0.00T F"1=968	4	3.1	210	271
4000	F"1+F"2=998 F"1+F"2+F"3=1000 CIBSE	6	4.6	94	121
α=42°	LG3 L<3000 cd/m ² at 65°	8	6.1	53	68

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	70	66	64	61	66	63	63	60	76
1.0	73	70	67	66	69	67	67	64	81
1.5	77	75	73	71	74	72	71	69	87
2.0	80	78	77	75	77	76	75	72	92
2.5	82	80	79	78	79	78	77	75	95
3.0	83	82	81	80	80	79	78	76	97
4.0	84	83	82	82	81	81	80	78	99
5.0	84	84	83	83	82	82	80	79	100

Luminance curve limit



Corre	ected UC	R value	s (at 320)) Im bar	e lamp lu	eu oni mu	flux)				
Rifle	ct.:										
ceil/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls work pl.		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
				0.20	0.20	0.20	0.20	0.20	0.20	0.20	
Room dim		viewed							viewed		
X	У	crosswise							endwise		
2H	2H	21.0	21.7	21.3	21.9	22.2	21.0	21.7	21.3	21.9	22.
	ЗН	20.9	21.5	21.2	21.8	22.0	20.9	21.5	21.2	21.8	22.
	4H	20.8	21.4	21.1	21.7	22.0	20.8	21.4	21.1	21.7	22.
	бН	20.7	21.2	21.1	21.6	21.9	20.7	21.2	21.1	21.6	21.
	HS	20.7	21.2	21.1	21.5	21.9	20.7	21.2	21.1	21.5	21.
	12H	20.7	21.1	21.0	21.5	21.8	20.7	21.1	21.0	21.5	21.
4H	2H	20.8	21.4	21.1	21.7	22.0	20.8	21.4	21.1	21.7	22
	ЗН	20.7	21.1	21.0	21.5	21.8	20.7	21.1	21.0	21.5	21.
	4H	20.6	21.0	21.0	21.4	21.7	20.6	21.0	21.0	21.4	21.
	бН	20.5	20.8	20.9	21.2	21.7	20.5	20.8	20.9	21.2	21.
	HS	20.4	20.8	20.9	21.2	21.6	20.4	20.8	20.9	21.2	21.
	12H	20.4	20.7	20.8	21.1	21.6	20.4	20.7	20.8	21.1	21.
вн	4H	20.4	20.8	20.9	21.2	21.6	20.4	20.8	20.9	21.2	21.
	6H	20.4	20.6	20.8	21.1	21.5	20.4	20.6	8.02	21.1	21
	HS	20.3	20.5	20.8	21.0	21.5	20.3	20.5	20.8	21.0	21.
	12H	20.3	20.5	20.8	20.9	21.5	20.3	20.5	20.8	20.9	21.
12H	4H	20.4	20.7	20.8	21.1	21.6	20.4	20.7	20.8	21.1	21.
	6H	20.3	20.5	20.8	21.0	21.5	20.3	20.5	20.8	21.0	21
	HS	20.3	20.5	20.8	20.9	21.5	20.3	20.5	20.8	20.9	21.
Varia	tions wi	th the ob	oserver p	osition	at spacin	g:					
S =	1.0H	5.1 / -14.3					5.1 / -14.3				
	1.5H	7.9 / -16.4					7.9 / -16.4				
	2.0H	9.9 / -17.8					9.9 / -17.8				