


Last information update: December 2024

**Product configuration: Q395**

Q395: Minimal Angular Module - General Down Light - Warm LED - DALI

**Product code**

Q395: Minimal Angular Module - General Down Light - Warm LED - DALI

**Technical description**

Angular element for Minimal (frameless) flush with ceiling version profiles; including a Neutral LED module. Methacrylate opal screen (diffused general light); screen set up for connecting several lengths by overlapping. Built-in DALI dimmable control gear. Pass-through wiring for continuous lines:

**Installation**

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately.

**Colour**

White (01) | Aluminium (12)

**Weight (Kg)**

5

**Mounting**

ceiling recessed|ceiling surface|ceiling pendant

**Wiring**

The angular profile is supplied with pass-through wiring for continuous lines. Quick coupling terminal blocks to simplify connections between the luminaires. LED module complete with integrated dimmable DALI control gear.

**Notes**

Take care when configuring the system; to complete a continuous line with an angular profile correctly, two initial modules are required, one for each side of the corner.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	3700	Colour temperature [K]:	3000
W system:	33	MacAdam Step:	3
lm source:	2500	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	15	Voltage [Vin]:	230
Luminous efficiency (lm/W, real value):	112.1	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	74	Number of optical assemblies:	2
CRI (minimum):	80	Control:	DALI-2

**Polar**

	Lux				
	h	d1	d2	Em	Emax
90°	2	4.9	5.1	106	178
750	4	9.8	10.2	27	45
0°	6	14.7	15.4	12	20
$\alpha = 102^\circ / 104^\circ$	8	19.6	20.5	7	11

**Isolux**

