

Last information update: July 2023

Product code

PF69: DALI-2 Touch Display 7" Plus

**Technical description**

Light management panel for DALI and DALI-2 luminaires, with 7-inch, 1024x600 px colour touchscreen - Controls TWRGB/RGBW/RGB/TW (DT8) and monochrome luminaires in broadcast mode with no programming. The TWRGB/RGBW/RGB/TW (DT8) and monochrome luminaires can be programmed to create groups/scenes/sequences. Circadian curve mode available for TW luminaires. This can be programmed via an intuitive menu directly from the touch panel - Functions: controls brightness, colour temperature and colours from palette, screen-configurable widgets, groups, scenes, sequences and weekly schedulers. Air quality sensors integrated in panel for local values display. Software updating via Ethernet and webpage. Background image that can be uploaded via Ethernet and webpage.

Installation

Mounted on a common wall-mounted, recessed 2-module box (passo 60 mm) or panel, using the flange included. Wall-mounted, recessed box accessory available (code ML15, to be ordered separately).

Colour

White (01)

Weight (Kg)

0.25

Mounting

wall recessed

Wiring

DA-DA line for connecting luminaires for a max of 64 DALI addresses.

The DA-DA line must be fitted with an accessory DALI power supply (code M630 available, to be ordered separately).

Line for 24 Vdc power supply input to connect an accessory power supply to (code 9908 available, to be ordered separately).

Eventual connection to a LAN/Ethernet via a RJ45 socket for updating and changing the background image and expanding the DALI addresses if necessary (for a compatible accessory, contact iGuzzini).

Notes

The panel remains visibly distanced from the wall/panel by leaving a space of about 8 mm for aesthetic reasons.

Complies with EN60598-1 and pertinent regulations

IP20

Technical data

Control: DALI-2