

**LINEALUCE**

**WALL-MOUNTING / PENDANT**

Luminaire designed to produce direct light with Led light sources and flood optic. Suitable for multiple locations: wall surface, ceiling pendant and surface. Nickel-plated brass cable clamp PG11 for single entry of power supply cable.

**#I.B - 15**


MODEL FINISH

**LAMPING:** 28 X 1W WHITE LED, FLOOD OPTIC  
(SEE MODEL)


**PROJECT NAME:** \_\_\_\_\_

**TYPE:** \_\_\_\_\_ **QTY:** \_\_\_\_\_

LAST UPDATE: APRIL 16, 2015



**TOP VIEW**



**FRONT VIEW**

**SIDE VIEW**

**IP 66**

**IK 05**

**MODEL**

☐ **I.B752** - 28 X 1W WARM WHITE LED, 3100K  
FLOOD OPTIC 32° BEAM

☐ **I.BB72** - 28 X 1W NEUTRAL WHITE LED, 4200K  
FLOOD OPTIC 32° BEAM

**ACCESSORIES (TO BE ORDERED SEPARATELY)**

**I.5506** - COLOURED FILTERS

- ☐ 02 - ORANGE
- ☐ 06 - YELLOW
- ☐ 26 - MAGENT
- ☐ D7 - CYAN

☐ **I.5510** - ANTI-GLARE SCREEN  
15 - GRAY

☐ **I.5571** - DIE-CAST ALUMINUM  
SUPORT PLATE

☐ **I.5573** - WALL MOUNTING BRACKET  
15 - GRAY

☐ **I.5576** - ADJUSTABLE ARMS +/- 90°  
15 - GRAY

☐ **I.5577** - EXTENDABLE ARM  
EXTEND FROM 12-3/16" TO 15-5/16"  
AND TURN THROUGH +/- 90°  
15 - GRAY

☐ **I.5578** - BALUSTRADE BRACKETS  
15 - GRAY

SUSPENSION CABLE (6'-6-3/4"L)

☐ **I.5588** WITHOUT POWER SUPPLY

☐ **I.5589** W/ POWER SUPPLY  
15 - GRAY

SUSPENSION ROD (1'-10-1/4"L)

☐ **I.5590** WITHOUT POWER SUPPLY

☐ **I.5591** W/ POWER SUPPLY  
15 - GRAY

**VOLTAGE**

☒ 120V

**FINISH**

☒ 15 - GRAY



9320 Boul. St-Laurent,  
suite 100, Montréal (Québec)  
Canada H2N 1N7  
P.: 514.523.1339 F.: 514.525.6107

**LINEALUCE**  
**WALL-MOUNTING / PENDANT**