

## SPECIFICATION SHEET

## LINEALUCE LED

### WALL / CEILING / PENDANT

**#1.B**            **-120-** 15  
LED FINISH  
COLOR


**LAMPING:** 27.9W LED, SPOT OPTIC,  
(SEE LED COLOR)

**PROJECT NAME:** \_\_\_\_\_


**TYPE:** \_\_\_\_\_ **QTY:** \_\_\_\_\_

LAST UPDATE : SEPTEMBER 11, 2014

LINEALUCE Led spot light can be surface mounted or pendant. Long lasting Leds make this lamp ideal for areas that are difficult to access.



### FRONT VIEW



### BOTTOM VIEW

### SIDE VIEW

**(IP 66 | IK 05)**

## LED COLOR

- ☐ **I.BB67** - 4200K LED, 1547 lm (delivered), 55 lm/w
- ☐ **I.B749** - 3200K LED, 1343 lm (delivered), 48 lm/w

## VOLTAGE

 120V

## METAL FINISH

 15 - GRAY

### ACCESSORIES (TO BE ORDERED SEPERATLY)

## I.5506 - COLOURED FILTERS

- ☐ 00 - FROSTED    ☐ 07 - GREEN  
☐ 05 - RED            ☐ 09 - BLUE  
☐ 06 - YELLOW

○ **I.5572** - BRACKET FOR WALL  
INSTALLATION

- 15 - GRAY

○ **I.5576** - ADJUSTABLE ARM +/- 90°  
15 - GRAY

○ **I.5577** - EXTENDABLE ARM +/- 90°

- 15 - GRAY

○ **I.5578** - BARCKET FOR BALUSTRADE  
INSTALLATION

- 
- 15 - GRAY

☐ **I.5588** - SUSPENSION CABLE WITHOUT  
POWER SUPPLY

- 6

○ **I.5589** - SUSPENSION CABLE WITH  
POWER SUPPLY

- 15 - GRAY

☐ **I.5590** - ROD WITHOUT POWER SUPPLY  
15 - GRAY

- 

○ **I.5591** - ROD WITH POWER SUPPLY  
15 - GRAY

- 



9320 Boul. St-Laurent,  
suite 100, Montréal (Québec)  
Canada H2N 1N7  
P.: 514.523.1339 F.: 514.525.6107

## LINEALUCE LED WALL / CEILING / PENDANT