

**LINEALUCE**

**WALL-MOUNTING / PENDANT**

Luminaire designed to produce direct light with LED light sources and spot optic. Suitable for multiple locations: wall surface, ceiling pendant and surface. Nickel-plated brass cable clamp PG11 for single entry of power supply cable.


**#I.B - 15**  
MODEL FINISH

**LAMPING:** 14 X 1W WHITE LED, SPOT OPTIC  
(SEE MODEL)


**PROJECT NAME:** \_\_\_\_\_

**TYPE:** \_\_\_\_\_ **QTY:** \_\_\_\_\_

LAST UPDATE: MAY 23, 2012



**TOP VIEW**



**FRONT VIEW**

STAINLESS STEEL FASTENERS AND ANCHOR POINTS FOR INSTALLATION SYSTEMS



**SIDE VIEW**

**IP 66**

**IK 05**

**MODEL**

☐ **I.B747** - 14 X 1W WARM WHITE LED, 3100K  
SPOT OPTIC 14° BEAM

☐ **I.BB66** - 14 X 1W NEUTRAL WHITE LED, 4200K  
SPOT OPTIC 14° BEAM

**ACCESSORIES (TO BE ORDERED SEPARATELY)**

**I.5504** - COLOURED FILTERS

- ☐ 02 - ORANGE ☐ D7 - CYAN  
☐ 06 - YELLOW  
☐ 26 - MAGENTA

☐ **I.5508** - ANTI-GLARE SCREEN  
15 - GREY

☐ **I.5570** - DIE-CAST ALUMINUM  
SUPORT PLATE

☐ **I.5572** - WALL MOUNTING BRACKET  
15 - GREY

☐ **I.5576** - ADJUSTABLE ARMS +/- 90°  
15 - GREY

☐ **I.5577** - EXTENDABLE ARM  
EXTEND FROM 12-3/16" TO 15-5/16"  
AND TURN THROUGH +/- 90°  
15 - GREY

☐ **I.5578** - BALUSTRADE BRACKETS  
15 - GREY

SUSPENSION CABLE (6'-6-3/4"L)

☐ **I.5588** WITHOUT POWER SUPPLY

☐ **I.5589** W/ POWER SUPPLY  
15 - GREY

SUSPENSION ROD (1'-10-1/4"L)

☐ **I.5590** WITHOUT POWER SUPPLY

☐ **I.5591** W/ POWER SUPPLY  
15 - GREY

**VOLTAGE**

☒ 120V

**FINISH**

☒ 15 - GREY



5455 de Gaspé  
suite 100, Montréal (Québec)  
Canada H2T 3B3  
P.: 514.523.1339 F.: 514.525.6107

**LINEALUCE**  
**WALL-MOUNTING / PENDANT**