

Last information update: April 2024

Product configuration: N379

N379: extractable, adjustable, recessed LED luminaire - DALI control gear included

**Product code**

N379: extractable, adjustable, recessed LED luminaire - DALI control gear included

Technical description

Extractable, adjustable, recessed luminaire for neutral white LED lamp. Passive heat dispersion system. Die-cast aluminium main body and frame; stainless steel rotation hinge. Rotation ring with safety cover in a high resistance thermoplastic material. Body adjusted with a manual manoeuvre device; internal 40° - external 65° - rotation on 355° axis. Reflector with high efficiency super-pure aluminium optic - flood beam angle. Die-cast aluminium lamp body closure ring. Tempered transparent glass screen. Dimmable DALI control gear supplied and connected to the luminaire.

Installation

recessed using steel springs in false ceilings with thicknesses starting at 1 mm

Colour	Weight (Kg)
White (01)	0.85


Mounting
ceiling recessed

Wiring
on control gear box with quick-coupling connections

Complies with EN60598-1 and pertinent regulations

**Technical data**


Im system:	1657	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W system:	14.6	Lamp code:	LED
Im source:	2100	Number of lamps for optical assembly:	1
W source:	12	ZVEI Code:	LED
Luminous efficiency (Im/W, real value):	113.5	Number of optical assemblies:	1
Im in emergency mode:	-	Power factor:	See installation instructions
Total light flux at or above an angle of 90° [Lm]:	0	Inrush current:	18 A / 250 µs
Light Output Ratio (L.O.R.) [%]:	79	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 21 luminaires B16A: 34 luminaires C10A: 35 luminaires C16A: 57 luminaires
Beam angle [°]:	42°	Minimum dimming %:	1
CRI (minimum):	80	Oversupply protection:	2kV Common mode & 1kV Differential mode
Colour temperature [K]:	4000	Control:	DALI-2
MacAdam Step:	2		

Polar

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	70	66	64	61	66	63	63	60	76
1.0	73	70	67	66	69	67	67	64	81
1.5	77	75	73	71	74	72	71	69	87
2.0	80	78	77	75	77	76	75	72	92
2.5	82	80	79	78	79	78	77	75	95
3.0	83	82	81	80	80	79	78	76	97
4.0	84	83	82	82	81	81	80	78	99
5.0	84	84	83	83	82	82	80	79	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 2100 lm bare lamp luminous flux)									
Reflect.:		viewed crosswise					viewed endwise		
ceil/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise		
X	Y								
2H	2H	19.6	20.2	19.8	20.5	20.7	19.6	20.2	19.8
	3H	19.4	20.0	19.7	20.3	20.6	19.4	20.0	19.7
	4H	19.3	19.9	19.7	20.2	20.5	19.3	19.9	19.7
	6H	19.3	19.8	19.6	20.1	20.4	19.3	19.8	19.6
	8H	19.2	19.7	19.6	20.1	20.4	19.2	19.7	19.6
	12H	19.2	19.7	19.6	20.0	20.4	19.2	19.7	19.6
4H	2H	19.3	19.9	19.7	20.2	20.5	19.3	19.9	19.7
	3H	19.2	19.7	19.6	20.0	20.4	19.2	19.7	19.6
	4H	19.1	19.5	19.5	19.9	20.3	19.1	19.5	19.5
	6H	19.0	19.4	19.5	19.8	20.2	19.0	19.4	19.5
	8H	19.0	19.3	19.4	19.7	20.2	19.0	19.3	19.4
	12H	18.9	19.2	19.4	19.7	20.1	18.9	19.2	19.4
8H	4H	19.0	19.3	19.4	19.7	20.2	19.0	19.3	19.4
	6H	18.9	19.2	19.4	19.6	20.1	18.9	19.2	19.4
	8H	18.8	19.1	19.3	19.5	20.0	18.8	19.1	19.3
	12H	18.8	19.0	19.3	19.5	20.0	18.8	19.0	19.5
12H	4H	18.9	19.2	19.4	19.7	20.1	18.9	19.2	19.4
	6H	18.8	19.1	19.3	19.5	20.0	18.8	19.1	19.3
	8H	18.8	19.0	19.3	19.5	20.0	18.8	19.0	19.5
Variations with the observer position at spacing:									
S =	1.0H	5.1 / -14.3				5.1 / -14.3			
	1.5H	7.9 / -16.4				7.9 / -16.4			
	2.0H	9.9 / -17.8				9.9 / -17.8			