iGuzzini

Last information update: May 2024

## Product configuration: P262

P262: Large body spotlight - Neutral white - DALI ballast - medium optic





P262: Large body spotlight - Neutral white - DALI ballast - medium optic Attention! Code no longer in production

# Technical description

Adjustable spotlight with adapter for installation on mains electrified track for high output LED lamp with monochrome emission in a neutral white (4000K) colour. DALI ballast. The luminaire is made of die-cast aluminium and thermoplastic material, allowing 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. The luminaire has mechanical aiming locks and graduated scales for both movements, operated using the same tool on two screws, one on the optic compartment and one on the adapter for the track. Spotlight equipped with accessory holding ring designed to contain a flat accessory. Another external component can also be applied, selected from directional flaps and an asymmetric screen. All external accessories rotate 360° about the spotlight longitudinal axis.

Weight (Kg)

2.25

## Installation On an electrified track

300 [62]

### Colour White (01) | Grey / Black (74)

Mounting

# three circuit track

Wiring

The DALI components are housed in the luminaire.



#### Technical data Im system: 3687 80 CRI (minimum): W system: 35 Colour temperature [K]: 4000 Im source: 5000 MacAdam Step: 3 LED 35 W source: Lamp code: Luminous efficiency (Im/W, 105.3 Number of lamps for optical 1 real value): assembly: Im in emergency mode: ZVEI Code: LED Total light flux at or above 0 Number of optical an angle of 90° [Lm]: assemblies Light Output Ratio (L.O.R.) 74 Control: DALI [%]: Beam angle [°]: 16°



