

Last information update: November 2024

**Product configuration: RR54**

RR54: Dimmable electronic Ø122mm DALI body - Medium optic - Neutral White



**Product code**

RR54: Dimmable electronic Ø122mm DALI body - Medium optic - Neutral White

**Technical description**

Adjustable spotlight with adapter for installation on an electrified track or base. High chromatic yield LED lamp with Neutral White (4000K) tone and OptiBeam Lens optic system and Medium optic. Dimmable electronic DALI power supply integrated in product. Luminaire made of die-cast aluminium and thermoplastic material that allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane with mechanical aiming locks. Passive heat dissipation. Spotlight with "Push&Go" system designed to hold up to two flat accessories at the same time. The same system can also be used to apply another external component selected from the directional flaps and anti-glare screen. All internal accessories rotate 360° about the spotlight longitudinal axis.

**Installation**

Installation on an electrified track or base.

**Colour**

White (01) | Black (04)

**Weight (Kg)**

2.13


**Mounting**

wall surface/ceiling surface

**Wiring**

Electronic components integrated in product

Complies with EN60598-1 and pertinent regulations



**Technical data**

lm system:	2736	CRI (minimum):	90
W system:	29.3	Colour temperature [K]:	4000
lm source:	3420	MacAdam Step:	2
W source:	26	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	93.4	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	80	Number of optical assemblies:	1
Beam angle [°]:	16°	Control:	DALI-2

**Polar**

