

## iN60 Evo Stand-alone

Design iGuzzini

iGuzzini

Last information update: February 2025

### Product configuration: RZ39.12

RZ39.12: Pendant-mounted Stand Alone LED - Up/Down - DALI - UGR<19 - LO - MMO - L=1200 - 30.2W 3806.4lm - 3500K - CRI 90 - Aluminium



### Product code

RZ39.12: Pendant-mounted Stand Alone LED - Up/Down - DALI - UGR<19 - LO - MMO - L=1200 - 30.2W 3806.4lm - 3500K - CRI 90 - Aluminium

### Technical description

Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. 3500K LED plate with direct (Down) and indirect (Up) light emission. Low Output (LO) version with controlled luminance emission ( $L \leq 3000 \text{ cd/m}^2$ ) ideal for environments with video monitors ( $\text{UGR} < 19$ ). The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Metallised polycarbonate raster. Pendant and power supply cables L=1500

### Installation

Pendant-mounted

### Colour

Aluminium (12)


Complies with EN60598-1 and pertinent regulations



IP20

CE

UK  
CA



### Technical data

lm system:	3806	Colour temperature [K]:	3500
W system:	30.2	MacAdam Step:	3
lm source:	4880	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	27	Lamp code:	LED
Luminous efficiency (lm/W, real value):	126	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	1349	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	78	Control:	DALI-2
CRI (minimum):	90		

### Polar

