

Blade R downlight



Design iGuzzini

iGuzzini

Last information update: October 2024

Product configuration: QS85

QS85: Minimal Ø 129 - Wide Flood beam - LED



Product code

QS85: Minimal Ø 129 - Wide Flood beam - LED

Technical description

Ring luminaire with 12 optical elements for LED lamps - fixed optics. The optic system guarantees a high level of visual comfort and no glare. The body includes a radiant surface made of die-cast aluminium. Minimal (frameless) version for flush with ceiling installation. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. High definition reflectors made of thermoplastic material vacuum-metallised with aluminium vapours, integrated in a set-back position in the anti-glare screen. Supplied with a power supply unit connected to the luminaire.

Installation

Recessed with steel wire springs for false ceilings from 12,5 to 25 mm thick - Ø 129 installation hole.

Colour

White (01) | Black (04) | Gold (14)* | Burnished chrome (E6)*

Weight (Kg)

0.54

* Colours on request

Mounting

ceiling recessed

Wiring

On the power supply unit with terminal board included. Available in DALI electronic versions.

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	2253	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
W system:	26.8	Voltage [Vin]:	230
lm source:	2650	Lamp code:	LED
W source:	24	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	84	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	85	Inrush current:	21 A / 139 µs
Beam angle [°]:	58°	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 15 luminaires B16A: 24 luminaires C10A: 24 luminaires C16A: 40 luminaires
CRI (minimum):	90	Minimum dimming %:	1
Colour temperature [K]:	4000	Overvoltage protection:	2kV Common mode & 1kV Differential mode
MacAdam Step:	2	Control:	DALI-2


Polar

Imax=3196 cd C80-260 90° 180° 90° 3000 0° α=58°	CIE		Lux	
	nL 0.85 100-100-100-100-85 UGR 12.3-12.4 DIN A.61 UTE 0.85A+0.00T F*1=997 F*1+F*2=1000 F*1+F*2+F*3=1000 CIBSE LG3 L<1500 cd/m ² at 65° UGR<16 L<1500 cd/mq @65°	h	d1	d2
	2	2.2	2.2	591 798
	4	4.4	4.4	148 199
	6	6.7	6.7	66 89
	8	8.9	8.9	37 50

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	77	73	70	68	72	70	69	67	78
1.0	80	77	74	72	76	73	73	70	83
1.5	84	81	79	78	80	79	78	75	89
2.0	87	85	83	82	84	82	81	79	93
2.5	88	87	86	85	86	85	84	81	96
3.0	89	88	87	87	87	86	85	83	98
4.0	90	90	89	89	88	88	86	84	99
5.0	91	90	90	90	89	89	87	85	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 2650 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	12.8	13.4	13.1	13.7	13.9	13.0	13.0	13.3	13.8	14.1
	3H	12.7	13.2	13.0	13.5	13.8	12.9	13.4	13.2	13.7	13.9
	4H	12.6	13.1	13.0	13.4	13.7	12.8	13.3	13.1	13.6	13.9
	6H	12.6	13.0	12.9	13.3	13.6	12.7	13.2	13.1	13.5	13.8
	8H	12.5	13.0	12.9	13.3	13.6	12.7	13.1	13.0	13.4	13.8
12H	12.5	12.9	12.9	13.2	13.6	12.6	13.1	13.0	13.4	13.7	
4H	2H	12.6	13.1	13.0	13.4	13.7	12.8	13.3	13.1	13.6	13.9
	3H	12.5	12.9	12.9	13.2	13.6	12.6	13.1	13.0	13.4	13.7
	4H	12.4	12.8	12.8	13.1	13.5	12.6	12.9	13.0	13.3	13.7
	6H	12.3	12.6	12.7	13.0	13.4	12.5	12.8	12.9	13.2	13.6
	8H	12.3	12.5	12.7	13.0	13.4	12.4	12.7	12.9	13.1	13.6
12H	12.2	12.5	12.7	12.9	13.4	12.4	12.6	12.8	13.1	13.5	
8H	4H	12.3	12.5	12.7	13.0	13.4	12.4	12.7	12.9	13.1	13.6
	6H	12.2	12.4	12.6	12.8	13.3	12.3	12.6	12.8	13.0	13.5
	8H	12.1	12.3	12.6	12.8	13.3	12.3	12.5	12.8	12.9	13.4
	12H	12.1	12.2	12.6	12.7	13.2	12.2	12.4	12.7	12.9	13.4
12H	4H	12.2	12.5	12.7	12.9	13.4	12.4	12.6	12.8	13.1	13.5
	6H	12.1	12.3	12.6	12.8	13.3	12.3	12.5	12.8	12.9	13.4
	8H	12.1	12.2	12.6	12.7	13.2	12.2	12.4	12.7	12.9	13.4
Variations with the observer position at spacing:											
S =	1.0H	6.8 / -31.1					6.8 / -31.1				
	1.5H	9.6 / -40.3					9.6 / -42.0				
	2.0H	11.6 / -51.6					11.6 / -48.9				