

Last information update: May 2025

Product configuration: S560

S560: 47 surface Integral with side box - RGBW (W=4000K) - DMX - L = 1,204mm - Wall Grazing Wide Flood optic

**Product code**

S560: 47 surface Integral with side box - RGBW (W=4000K) - DMX - L = 1,204mm - Wall Grazing Wide Flood optic

Technical description

Direct light luminaire, designed to use RGBW LED lamps, (W=4000K), 220÷240Vac DMX512-RDM dimmable with searching and addressing function. Ceiling, wall or surface-mounted. It consists of a body and installation brackets to be ordered separately. The body is made of extruded aluminium and includes die-cast aluminium end caps with 50/60 Shore A silicone seals. It is subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED power plate in RGBW colour and a 220÷240Vac DMX512-RDM electronic driver (power supply included). Supplied with a double PG13.5 cable gland and outlet cables for pass-through wiring with IP68 male/female connectors. Fitted with a PMMA diffusing filter and optics with a plastic (methacrylate) lens for Wide Flood lighting. All external screws used are made of A2 stainless steel.

Installation

Installation accessories can be purchased separately, including arms (for heights < 3m and heights > 3m) and plates.

Colour

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

Weight (Kg)

4.05

Mounting

wall arm|wall surface



Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	1846	Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)
W system:	37.1	Life Time LED 2:	96,000h - L80 - B10 (Ta 40°C)
Im source:	2840	Voltage [Vin]:	230
W source:	28	Lamp code:	LED
Luminous efficiency (Im/W, real value):	49.8	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	65	Intervallo temperatura ambiente:	from -30°C to 50°C.
CRI (typical):	82	Control:	DMX-RDM
Colour temperature [K]:	RGBW - 4000K		

Polar