


Ultimo aggiornamento delle informazioni: Ottobre 2024

Configurazione di prodotto: BJ41

BJ41: Wall-/Ceiling-mounted - 18 Neutral White LEDs - 24V/500mA dc - L=1585mm - Wall Grazing Optic

**Codice prodotto**

BJ41: Wall-/Ceiling-mounted - 18 Neutral White LEDs - 24V/500mA dc - L=1585mm - Wall Grazing Optic

Descrizione tecnica

Direct light luminaire, designed to use monochrome LED lamps. Ceiling- and wall-mounted. Consists of a body and supports for installation (to be ordered separately). Extruded aluminium body, with zamak die-cast end caps complete with silicone seals. Coated with liquid acrylic paint with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED power plate in Neutral White 4000K with 24V/500mA dc electronic circuit (ballast to be ordered separately); 24V/500mA smart driver allowing constant light flow emission despite variations in the input voltage (from 30V dc to 16V dc). Fitted with a PMMA diffusing filter and optic with plastic (methacrylate) lens for Wall Grazing lighting. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN 60598-1 standards and particular requirements.

Installazione

The following accessories are available for installation: adjustable wall-mounted arms in AISI304 stainless steel (L=83mm code BZJ9, 200mm code BZJ8) and a plate for surface- or ceiling-mounting made of anodised aluminium (BZJ7).

Colore

Grigio (15)

Peso (Kg)

2.22

Montaggio

a parete|a soffitto

Cablaggio

The product is supplied with a single nickel-plated brass cable gland PG9 and a 2x1mm² PVC and polyurethane outlet cable, 2000mm long. For the electrical connection there is an IP68 linear connector (BZK6) and an IP66 junction box with quick-coupling terminals (BZK7). 24V/500mA dc electronic power supply to be ordered separately: 32W (BZA0), and 35W (BZM4)

Note


Product complete with LED lamp.

Soddisfa EN60598-1 e relative note

**Dati tecnici**

Im di sistema:	1288	MacAdam Step:	3
W di sistema:	28	Life Time LED 1:	66,000h - L80 - B10 (Ta 25°C)
Im di sorgente:	2380	Life Time LED 2:	66,000h - L80 - B10 (Ta 40°C)
W di sorgente:	28	Codice lampada:	LED
Efficienza luminosa (lm/W, dati di sistema):	46	Numero di lampade per vano ottico:	1
Im in modalità emergenza:	-	Codice ZVEI:	LED
Flusso totale emesso a 90° o superiore [Lm]:	0	Numero di vani ottici:	1
Light Output Ratio (L.O.R.) [%]:	54	Intervallo temperatura ambiente operativa:	da -30°C a 50°C.
CRI (minimo):	80	Corrente LED [mA]:	500
Temperatura colore [K]:	4000		

Polare



Illuminanti

Lux		Wall distance = 1m										
3						●						
		0.2	0.4	0.9	3	6	9	7	3	1	0.5	0.2
2	—	1	2	5	10	17	24	19	11	6	3	1
		2	4	7	13	21	27	24	15	8	4	2
1	—	3	4	7	14	21	28	24	16	9	5	3
		3	5	8	13	19	25	21	14	9	5	3
0												
	m	-2	-1	0	1	2	3					