


Last information update: October 2020

**Product code**

EU99: Spotlight with bracket (to be ordered separately) - Warm White LED - Remote Ballast - Wide Flood optic - Ta 25°

Technical description

Spotlight designed to use LED lamps and a Wide Flood optic. Consists of a die-cast aluminium optical assembly and brackets (both the bracket for the spotlight and the bracket for handle/pole application) with a clear tempered sodium-calcium safety glass cover. It is fitted with an A2 stainless steel cable gland and a 2x1mm² section 05RN-F cable. The optical assembly can be adjusted on a horizontal plane at an angle between -50° / +90°. Agorà is fitted with a graduated scale and mechanical locking device for positioning. The Opti Beam Lens optical system comes complete with a Warm White monochrome LED circuit. The electronic DALI ballast is remote and can be ordered separately to allow the spotlights to be connected in series. The spotlight is fitted with a protection system that in the event of a fault allows all the other products in the same circuit to operate normally. Class I, IP67 rated power supply units must be used (all the necessary information is included in the instruction sheet). Both indoor (diffuser glass covers, lamellar louvers and refractors for elliptical light) and outdoor accessories (cylindrical screens, visors and protective grilles) can be used. All external screws used are made of A2 stainless steel.

Installation

Floor-installed or wall-mounted with a bracket or handle (special bracket).

Colour

Grey (15)

Wiring

A2 stainless steel cable gland.

Complies with EN60598-1 and pertinent regulations



IK08

IP67

EAC

**Technical data**

Im system:	-	CRI:	0
W system:	-	Colour temperature [K]:	2700
Im source:	-	Number of lamps for optical assembly:	1
W source:	-	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Beam angle [°]:	40 (*)	Ambient operating temperature range:	from -20 °C to +35 °C. (*)

* Preliminary data