


Last information update: October 2024



Product code

R093: 5-cell recessed luminaire - LED - Warm White - longitudinal optic

Technical description

Rectangular miniaturised recessed luminaire with 5 optical elements fitted with LED lamps - fixed optics - "oval" light effect. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. High definition, metallised thermoplastic optics installed in a set-back position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect. Supplied with electronic control gear unit connected to the luminaire.

Installation

recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 141

Colour

White (01) | Black / Black (43) | Black / White (47) | Grey / Black (74)*

* Colours on request

Mounting

ceiling recessed

Wiring

on control gear box; screw connections with terminal block included

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	-	CRI:	95
W system:	-	Colour temperature [K]:	3000
lm source:	-	Number of lamps for optical assembly:	1
W source:	-	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	69.17 (*)	Number of optical assemblies:	1
lm in emergency mode:	-	Control:	On/off
Beam angle [°]:	40°-85° (*)		