



Last information update: May 2024

Product configuration: 4872+1639

4872: Projector with 75 W QR 111 dimmable electronic transformer

**Product code**4872: Projector with 75 W QR 111 dimmable electronic transformer **Attention! Code no longer in production****Technical description**

Die-cast aluminium and thermoplastic projector with adapter. It can be rotated by 340° with respect to the vertical axis and inclined by +/- 100° with respect to the horizontal axis. Rotation and inclination movements may be locked mechanically to guarantee precise positioning of the light beam - also during maintenance operations. IP40 for optical assembly with optional glass diffusers.

Installation

Track mounted or ceiling/wall mounted by means of the base to be ordered separately.

Colour

White (01) | Grey / Black (74)

Mounting

three circuit track

Wiring

Complete with dimmable electronic transformer for 75W 12V halogen lamps, inside the luminaire.

Notes

The luminaire becomes IP40 with the use of accessory glasses. For the photometric data of the luminaire, refer to the photometric characteristics of the light source.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	796	CRI (minimum):	100
W system:	82	Colour temperature [K]:	3000
lm source:	796	Lamp maximum intensity [cd]:	1700
W source:	75	Voltage [Vin]:	12
Luminous efficiency (lm/W, real value):	9.7	Lamp code:	1639
lm in emergency mode:	-	Socket:	G53
Total light flux at or above an angle of 90° [Lm]:	0	Number of lamps for optical assembly:	1
Light Output Ratio (L.O.R.) [%]:	100	ZVEI Code:	QR 111
Beam angle [°]:	42°	Number of optical assemblies:	1

Polar