

---

**Platea Pro**

**Design Jean-Michel Wilmotte** **iGuzzini**

iGuzzini

Last information update: April 2024

## Product configuration: P817

P817: Platea Pro



## Product code

P817: Platea Pro

## Technical description

Outdoor luminaire with a Wall Washer optic, designed to use LED lamps. Made up of an optical assembly with a base and an aluminium alloy frame. The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. With a 5 mm thick colourless transparent tempered sodium-calcium glass cover. The product can be tilted by +5°/-90° around the vertical plane with a 10° step graduated gauge and fitted with mechanical blocks that guarantee stable aiming of the beam of light. Horizontal aiming is performed using the slots in the base, which allow an ±30° adjustment. High visual comfort. Polymer optic lenses offering high yield and even light distribution. Complete with circuit fitted with Warm White monochrome power LEDs. Extractable control gear connected with quick-coupling connectors. 220-240V ac 50/60Hz DALI electronic ballast. Replaceable control gear. All the screws used are made of A2 stainless steel.

## Installation

The luminaire can be installed at ground level or on walls using the standard base.

Colour	Weight (Kg)
--------	-------------

White (01)   Black (04)   Grey (15)   Rust Brown (F5)	8.55
---	------

## Weight (Kg)

8.55

## Mounting

wall arm|wall surface|ground anchored

---

**Wiring**

Luminaire ready for pass-through wiring. Product perfect watertightness at the power cable entry point is guaranteed by 2 nickel-plated brass M24x1.5 cable clamps, suitable for cables with a max external 16mm Ø (1.5mm² cross section). Push in terminal board.

---

Notes

Available accessories include: a refractor for elliptical light flow distribution, diffusing glass, visor, directional flaps, protective grille .


Complies with EN60598-1 and pertinent regulations



## Technical data

Im system:	4256	Life Time LED 2:	87,000h - L80 - B10 (Ta 40°C)
W system:	55.4	Lamp code:	LED
Im source:	6450	Number of lamps for optical assembly:	1
W source:	51	ZVEI Code:	LED
Luminous efficiency (Im/W, real value):	76.8	Number of optical assemblies:	1
Im in emergency mode:	-	Intervallo temperatura ambiente:	from -30°C to 50°C.
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	66	Inrush current:	62 A / 202 µs
CRI (minimum):	80	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 6 luminaires B16A: 10 luminaires C10A: 10 luminaires C16A: 17 luminaires
Colour temperature [K]:	3000	Minimum dimming %:	10
MacAdam Step:	3	Overvoltage protection:	10kV Common mode & 6kV Differential mode
Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)	Control:	DALI-2

Polar



Illuminances

Lux												Wall distance = 1m	
3													
	0.2	0.9	4	21	87	167	87	21	4	0.9	0.2		
2	3	7	23	82	273	519	273	82	23	7	3		
	6	14	41	136	391	615	391	136	41	14	6		
1	9	20	50	135	286	383	286	135	50	20	9		
	10	24	55	115	191	236	191	115	55	24	10		
0													
	m	-2	-1	0	1	2	3						