


Last information update: May 2024

Product configuration: EH44

EH44: Medium body spotlight without bracket - Warm White - ST1 optic

**Product code**EH44: Medium body spotlight without bracket - Warm White - ST1 optic **Attention! Code no longer in production****Technical description**

Outdoor luminaire with high visual comfort (G6) down light street optic, designed to use LED lamps. Painted die-cast aluminium body fitted with a 4 mm thick tempered sodium-calcium closing glass, secured to the frame. The optical assembly and the pole attachment system are made of EN1706AC 46100LF aluminium alloy, subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather resistance. The optical assembly is also fitted with a silicone sealed closing glass at the front to guarantee it is watertight and liquids cannot penetrate it. The frame has special slots for rainwater drainage. The luminaire is fitted with a double cable gland (M24x1,5) for pass-through wiring. MaxiWoody can be tilted on the vertical plane thanks to a bracket with a 10° step graduated scale, fitted with mechanical blocks that guarantee stable light beam aiming. Horizontal aiming is performed using a plate secured to the ground with slots and screw holes. Thanks to a decompression valve, access to the optical assembly is easy as it eliminates the internal vacuum. All the components are positioned on a single plate using captive screws so extraordinary maintenance is extremely rapid. The patented Optismart optic system comes complete with a power monochrome Neutral White LED circuit and silver aluminium reflectors. LEDs can be substituted in the lab in groups of 12. Selv electronic control gear. DALI electronic control gear. Midnight mode (100%-70%) or Bi-energy operation without external programming. Personalised Midnight programmable, fixed dimming, compatibility with flux regulators, via a special programming interface. Replaceable control gear. There is no light dispersion into the upper hemisphere above this luminaire in the horizontal position (in conformity with the strictest standards for the prevention of light pollution). All external screws are made of stainless steel.

Installation

The device can be installed in CityWoody and linear FrameWoody systems.

Colour

Grey (15)

Weight (Kg)

10.7

Mounting

wall arm/wall surface

Wiring

The product is powered by cables from a pre-wiring box with 4-pin terminal board and resistance to mains voltage spikes up to 4KV (Varistor). Product perfect watertightness is guaranteed at the power cable entry point by a double PG M24x1.5 mm cable gland made of thermoplastic material with a thrust ring and rubber gasket that together achieve a class II insulation rating.


Complies with EN60598-1 and pertinent regulations

**Technical data**


Im system:	5810	MacAdam Step:	3
W system:	55.9	Life Time LED 1:	100,000h - L90 - B10 (Ta 25°C)
Im source:	-	Life Time LED 2:	44,000h - L90 - B10 (Ta 40°C)
W source:	-	Life Time LED 3:	100,000h - L80 - B10 (Ta 40°C)
Luminous efficiency (Im/W, 103.9 real value):		Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	100	Number of optical assemblies:	1
CRI (minimum):	70	Intervallo temperatura ambiente:	from -20°C to +35°C. (*)
Colour temperature [K]:	3000	Control:	DALI

* Preliminary data

Polar



Isolux



Utilisation factors

