



Last information update: October 2024



**Product code**

2202: Recessed Frame section 10 LEDs - integrated DALI - Wall Washer Longitudinal Glare Control

**Technical description**

Miniaturized recessed linear luminaire for LED lamps. Asymmetrical optic system designed to achieve effective light distribution on walls and avoid any shadow zones near the ceiling. The black polycarbonate perimeter frame is designed to significantly reduce the effect of longitudinal glare. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Flux enhancer - superpure aluminium reflector - textured PMMA screen. Supplied with a power supply unit connected to the luminaire.

**Installation**

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 274. To light walls correctly check the installation distances and centre-to-centre distances indicated on the instructions sheet.

**Colour**

Black / Black (43) | Black / White (47)


**Mounting**

wall recessed|ceiling recessed

**Wiring**

Integrated dimmable DALI control gear. Connection to mains network on power supply box; screw connections.

Complies with EN60598-1 and pertinent regulations



**Technical data**

lm system:	-	Colour temperature [K]:	2700
W system:	21 (*)	Number of lamps for optical assembly:	1
lm source:	-	ZVEI Code:	LED
W source:	21 (*)	Number of optical assemblies:	1
lm in emergency mode:	-	Control:	DALI-2
CRI:	90		