

## Laser Blade


Design iGuzzini

iGuzzini

Last information update: May 2024

**Product configuration: MQ45**

MQ45: adjustable 10-cell module - LED - integrated DALI dimmable control gear - neutral white - beam 48°



## Product code

**MQ45:** adjustable 10-cell module - LED - integrated DALI dimmable control gear - neutral white - beam 48° **Attention! Code no longer in production**

### Technical description

Adjustable linear module with LEDs, specifically designed to be housed in the Laser Blade System channel. The steel coupling plate includes the lighting group and the operating components. Module with 10 lighting cells, in die-cast aluminium, adjustable with a practical extraction and rotation system with max inclination +/- 45°. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled luminance (UGR < 19). Supplied with DALI dimmable control gear connected to the luminaire. Neutral white LED - lifetime with residual flow at 80% (L80): 50.000 hours - Ta 25°.

## Installation

Double rotating pin blocking system with return spring to facilitate the insertion in the profile seating. Can be manoeuvred with a screwdriver.

**Colour**  
Black (04)

Weight (Kg)  
1.3

## Mounting

ceiling recessed

## Wiring

The module is fitted with connectors on both sides for connecting with subsequent modules. For connections at greater distances, there are accessory connectors (code MXN6 - cables not included).

## Notes

dimming function with pushbutton (TOUCH DIM/PUSH): for this option consult the instructions included in the package


Complies with EN60598-1 and pertinent regulations



## Technical data

Im system:	1659	CRI:	95
W system:	24.5	Colour temperature [K]:	4000
Im source:	2000	MacAdam Step:	3
W source:	21	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	67.7	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	83	Number of optical assemblies:	1
Beam angle [°]:	48°	Control:	DALI

## Polar



# Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	79	77	76	79	77	76	74	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	86	85	83	100

# UGR diagram

Corrected UGR values (at 2000 lm bare lamp luminous flux)											
Riflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	1.8	2.3	2.1	2.5	2.8	1.8	2.3	2.1	2.5	2.8
	3H	1.7	2.1	2.0	2.4	2.7	1.7	2.1	2.0	2.4	2.7
	4H	1.6	2.0	2.0	2.3	2.6	1.6	2.0	2.0	2.3	2.6
	6H	1.6	1.9	1.9	2.3	2.6	1.6	1.9	1.9	2.2	2.6
	8H	1.5	1.9	1.9	2.2	2.5	1.5	1.9	1.9	2.2	2.5
	12H	1.5	1.8	1.9	2.2	2.5	1.5	1.8	1.9	2.2	2.5
4H	2H	1.6	2.0	2.0	2.3	2.6	1.6	2.0	2.0	2.3	2.6
	3H	1.5	1.8	1.9	2.2	2.5	1.5	1.8	1.9	2.2	2.5
	4H	1.4	1.7	1.8	2.1	2.5	1.4	1.7	1.8	2.1	2.5
	6H	1.3	1.6	1.7	2.0	2.4	1.3	1.6	1.7	2.0	2.4
	8H	1.3	1.5	1.7	1.9	2.4	1.3	1.5	1.7	1.9	2.4
	12H	1.2	1.4	1.7	1.9	2.3	1.2	1.4	1.7	1.9	2.3
8H	4H	1.3	1.5	1.7	1.9	2.4	1.3	1.5	1.7	1.9	2.4
	6H	1.2	1.4	1.6	1.8	2.3	1.2	1.4	1.6	1.8	2.3
	8H	1.1	1.3	1.6	1.8	2.3	1.1	1.3	1.6	1.8	2.3
	12H	1.1	1.2	1.6	1.7	2.2	1.1	1.2	1.6	1.7	2.2
12H	4H	1.2	1.4	1.7	1.9	2.3	1.2	1.4	1.7	1.9	2.3
	6H	1.1	1.3	1.6	1.8	2.3	1.1	1.3	1.6	1.8	2.3
	8H	1.1	1.2	1.6	1.7	2.2	1.1	1.2	1.6	1.7	2.2
Variations with the observer position at spacing:											
S =		0.9 / -18.0					0.9 / -18.0				
		1.5H					9.7 / -18.3				
		2.0H					11.7 / -18.4				