

Deep Frame



Design iGuzzini

iGuzzini

Last information update: October 2023

Product configuration: P897

P897: Deep Frame - 1 element - CoB warm LED - spot beam - dimmable DALI



Product code

P897: Deep Frame - 1 element - CoB warm LED - spot beam - dimmable DALI **Attention! Code no longer in production**

Technical description

Individual recessed luminaire for LED lamp. Version with a perimeter frame. Shaped sheet steel structural frame. Die-cast aluminium, twin swivel universal joint located in a position set back from the installation surface to guarantee a high level of visual comfort. Tilts $\pm 30^\circ$ around both the horizontal and vertical axes. Die-cast aluminium lighting body designed to optimise heat dispersal. High efficiency aluminium reflector - spot angle. High color rendering index, warm white LED lamp. Glass cover The installation system is toolfree. DALI dimmable control gear unit included.

Installation

Recessed in 1 to 30 mm thick false ceilings. Steel wire fixing springs. Preparation hole 102 x 102.

Colour

White (01) | Grey / Black (74)

Mounting

ceiling recessed


Wiring

Complete with DALI dimmable control gear unit connected to the luminaire. Wiring for connecting to mains network on driver terminal board.

Notes

Accessories available: refractor for elliptical flow distribution - interchangeable reflectors.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	656	Colour temperature [K]:	3000
W system:	10.7	MacAdam Step:	3
Im source:	950	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
W source:	8.4	Ballast losses [W]:	2.3
Luminous efficiency (Im/W, real value):	61.3	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	69	Number of optical assemblies:	1
Beam angle [°]:	18°	Control:	DALI
CRI (minimum):	90		


Polar

--

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	62	59	57	55	58	56	56	54	78
1.0	65	62	60	58	61	59	59	57	82
1.5	68	66	64	63	65	64	63	61	88
2.0	70	69	67	66	68	67	66	64	93
2.5	72	70	69	69	69	68	68	66	95
3.0	72	72	71	70	70	70	69	67	97
4.0	73	73	72	72	71	71	70	68	99
5.0	74	73	73	73	72	72	71	69	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 950 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	1.4	3.5	1.8	3.8	4.2	1.4	3.5	1.8	3.8	4.2
	3H	1.3	2.9	1.7	3.2	3.6	1.4	2.9	1.7	3.3	3.6
	4H	1.3	2.6	1.6	2.9	3.3	1.3	2.6	1.7	3.0	3.3
	6H	1.2	2.2	1.6	2.6	2.9	1.3	2.3	1.7	2.6	3.0
	8H	1.2	2.2	1.6	2.6	2.9	1.2	2.3	1.6	2.6	3.0
	12H	1.1	2.2	1.5	2.5	2.9	1.2	2.2	1.6	2.6	3.0
4H	2H	1.3	2.6	1.7	3.0	3.3	1.3	2.6	1.6	2.9	3.3
	3H	1.2	2.3	1.6	2.6	3.0	1.2	2.3	1.6	2.6	3.0
	4H	1.1	2.2	1.5	2.6	3.0	1.1	2.2	1.5	2.6	3.0
	6H	0.7	2.5	1.2	2.9	3.4	0.7	2.5	1.2	2.9	3.4
	8H	0.6	2.5	1.1	3.0	3.5	0.6	2.5	1.1	3.0	3.5
	12H	0.5	2.5	1.0	3.0	3.5	0.5	2.5	1.0	2.9	3.5
8H	4H	0.6	2.5	1.1	3.0	3.5	0.6	2.5	1.1	3.0	3.5
	6H	0.5	2.3	1.0	2.8	3.3	0.5	2.3	1.0	2.8	3.3
	8H	0.5	2.1	1.0	2.6	3.1	0.5	2.1	1.0	2.6	3.1
	12H	0.7	1.6	1.2	2.1	2.7	0.7	1.6	1.2	2.1	2.7
12H	4H	0.5	2.5	1.0	2.9	3.5	0.5	2.5	1.0	3.0	3.5
	6H	0.5	2.1	1.0	2.6	3.1	0.5	2.1	1.0	2.6	3.1
	8H	0.7	1.6	1.2	2.1	2.7	0.7	1.6	1.2	2.1	2.7
Variations with the observer position at spacing:											
S =	1.0H	3.4 / -4.4					3.4 / -4.4				
	1.5H	5.9 / -6.9					5.9 / -6.9				
	2.0H	7.9 / -10.8					7.9 / -10.8				