Design iGuzzini

iGuzzini

Last information update: April 2025

Product configuration: R351.01

R351.01: body Ø 117 mm - spot optic - 38.1W 4709lm - 4000K - White



Product code

R351.01: body Ø 117 mm - spot optic - 38.1W 4709lm - 4000K - White

Technical description

Adjustable mediumlight with adapter for installation on a mains voltage track. Luminaire made of die-cast aluminium. mediumlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Built-in dimmable DALI ballast. Luminaire complete with C.O.B. technology LED unit in neutral white colour 4000K. Anti-scratch reflector made of P.V.D (physical vapour deposition) aluminium that can provide optimum performance in terms of light efficiency. medium optic. Possibility of installing a flat accessory, like a glass cover or an elliptical distribution refractor. Interchangeable reflectors that can be ordered as an accessory.

Installation

On an electrified track or special base

 Colour
 Weight (Kg)

 White (01)
 1.1



three circuit track

Wiring

Product complete with DALI components

Complies with EN60598-1 and pertinent regulations



IP20



With accessory installed













174

Technical data			
Im system:	4709	CRI (minimum):	80
W system:	38.1	Colour temperature [K]:	4000
Im source:	5540	MacAdam Step:	2
W source:	34	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W,	123.6	Lamp code:	LED
real value):		Number of lamps for optical	1
Im in emergency mode:	-	assembly:	
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
		Number of optical	1
Light Output Ratio (L.O.R.) [%]:	85	assemblies:	
		Control:	DALI-2
Beam angle [°]:	22°		

Polar

Imax=24897 cd	Lux			
90° 180° 90°	h	d	Em	Emax
	2	0.7	4988	6209
	4	1.5	1247	1552
28000	6	2.2	554	690
α=21° /22°	8	3	312	388