Design iGuzzini

iGuzzini

Last information update: December 2023



Accessory code

MY83: Constant current power supply unit 1-10V IP20 50W - VIN = 220-240VAC 50/60Hz Ø25

Technical description

Dimmable 1-10V electronic ballast - constant current operation. Protection devices: thermal/short circuit - mains overvoltage overloads.

remote installation - including securing slots with screws.

Colour Indeterminate (00)	Weight (Kg) 0.21	Dimension (mm) (*) 124x79x22
		* The dimensions may change according to production requirements
		to ensure that performance levels and installation methods are
		observed.

Wiring
700 mA for Ø25 Laser recessed luminaires - min 2 - max 20 used. Palco Recessed-Surface - Ø19 / 700 mA max 22 - Ø37 / 650 mA max 5 - Ø51 / 1050 mA max 3. Cables secured with quick connection terminals.

Complies with EN60598-1 and pertinent regulations

B10A: 9 power supply units B16A: 15 power supply units





Technical data

Frequency [Hz]: 0/50/60 Current out [mA]: 350 Inrush current: $20~\text{A}\,/\,400~\mu\text{s}$ Maximum number of LED power supply units of this

type per miniature circuit breaker:

C10A: 15 power supply units C16A: 25 power supply units Overvoltage protection: 4kV Common mode & 4kV Differential mode