

Coefficients d'utilisation

R	77	75	73	71	55	53	33	00	DRR
K0.8	71	68	65	63	67	65	64	62	78
1.0	75	71	69	67	70	68	68	66	83
1.5	78	76	74	72	75	73	72	70	89
2.0	81	79	77	76	78	76	76	73	93
2.5	82	81	80	79	80	79	78	76	96
3.0	83	82	81	81	81	80	79	77	98
4.0	84	83	83	82	82	82	80	79	99
5.0	84	84	84	83	83	82	81	79	100

Courbe limite de luminance




Diagramme UGR

Corrected UGR values (at 1850 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling	cav	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	3.0	5.1	3.4	5.5	5.8	3.0	5.1	3.4	5.5	5.8
	3H	2.9	4.5	3.2	4.8	5.1	2.9	4.5	3.2	4.8	5.1
	4H	2.8	4.1	3.2	4.5	4.8	2.8	4.1	3.2	4.5	4.8
	6H	2.8	3.8	3.2	4.1	4.5	2.8	3.8	3.1	4.1	4.5
	8H	2.7	3.8	3.1	4.1	4.5	2.7	3.7	3.1	4.1	4.5
12H	2.7	3.7	3.1	4.1	4.5	2.7	3.7	3.1	4.0	4.4	
4H	2H	2.8	4.1	3.2	4.5	4.8	2.8	4.1	3.2	4.5	4.8
	3H	2.7	3.7	3.1	4.1	4.4	2.7	3.7	3.1	4.1	4.4
	4H	2.5	3.6	3.0	4.0	4.4	2.5	3.6	3.0	4.0	4.4
	6H	2.2	3.9	2.7	4.3	4.8	2.2	3.9	2.7	4.3	4.8
	8H	2.1	4.0	2.6	4.4	4.9	2.1	4.0	2.6	4.4	4.9
12H	2.0	4.0	2.5	4.4	5.0	2.0	3.9	2.5	4.4	4.9	
8H	4H	2.1	4.0	2.6	4.4	4.9	2.1	4.0	2.6	4.4	4.9
	6H	2.0	3.8	2.5	4.2	4.8	2.0	3.8	2.5	4.3	4.8
	8H	2.0	3.6	2.5	4.1	4.6	2.0	3.6	2.5	4.1	4.6
	12H	2.2	3.2	2.7	3.7	4.2	2.1	3.1	2.7	3.6	4.2
12H	4H	2.0	3.9	2.5	4.4	4.9	2.0	4.0	2.5	4.4	5.0
	6H	2.0	3.5	2.5	4.0	4.6	2.0	3.6	2.5	4.1	4.6
	8H	2.1	3.1	2.7	3.6	4.2	2.2	3.2	2.7	3.7	4.2
Variations with the observer position at spacing:											
S =	1.0H	6.9 / -11.5					6.9 / -11.5				
	1.5H	9.7 / -11.7					9.7 / -11.7				
	2.0H	11.7 / -11.8					11.7 / -11.8				